

XLED PRO 240 S neutralweiss schwarz



Product code **4007841068363**

E-Nr. **941502189**

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra ≥ 80
- Optional corner wall mount bracket
- Interconnectable by cable (maximum of 10 units)

neva
lux

161 x 180 x 223 mm



XLED PRO 240 S neutralweiss schwarz

Product code 4007841068363
E-Nr. 941502189

Technical Data

DIMENSIONS		Networking via		Cable		Settings via		Potentiometers			
Dimensions L × W × H		161 x 180 x 223 mm		Networking quantity		maximum of 10 floodlights		Twilight setting teach		No	
ELECTRICAL		LIGHTING TECHNOLOGY		HOUSING & MATERIAL							
Mains connection		220 – 240 V / 50 – 60 Hz		Measured luminous flux		2124 lm		Impact resistance		IK03	
Power		19,3 W		360°				Protection class (IP)		IP44	
SENSOR TECHNOLOGY		Colour temperature		4000 K		Protection class		II			
Max. mounting height		6,00 m		LED colour deviation		SDCM3		Ambient temperature		-20 – 40 °C	
Sensor technology		passive infrared		With illuminant		Yes, STEINEL LED system		Housing material		HCMC	
With motion detector		Yes		Illuminant		LED cannot be replaced		Cover material		Plastic, opal	
Detection angle		240 °		Base		without		Cover material (scope of delivery)		shrouds	
Opening angle		180 °		LED cooling system		HCMC (High Conductive Magnesium Composite)		Mounting location		corner wall	
Sneak-under protection		Yes		Soft light start		No		Application location		Outdoors	
Segment-by-segment masking		Yes		Continuous light		selectable		Mounting type		Surface wiring	
		LIFETIME						Application room		all round the building courtyard & driveway outdoors terrace / balcony	
Electronic scalability		No		LED lifetime L70B50 25°C		> 60000 h		SCOPE OF DELIVERY & WARRANTY			
Mechanical scalability		No		SETTINGS				Manufacturer warranty		5 years	
Radial range		r = 3 m (19 m²)		Twilight switch		Yes		Corner wall bracket included		No	
Tangential range		r = 12 m (302 m²)		Twilight setting		2 – 2000 lx		CERTIFICATES & EPREL			
Mounting height		1,80 – 6 m		Time setting		10 s – 15 Min.		EPREL category		Light source	
Optimal mounting height		2 m		Base light function		No					
CONNECTIVITY				Main light adjustable		No					
Networking		Yes									

XLED PRO 240 S neutralweiss schwarz

Product code 4007841068363
E-Nr. 941502189

Illustrations

MOUNTING HEIGHT

1,80 – 6 m BEREICH	2 m OPTIMAL	6,00 m MAX
-----------------------	----------------	---------------

XLED PRO 240 S neutralweiss schwarz

Product code **4007841068363**E-Nr. **941502189**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841068363

E-Number 941502189

Typ **XLED PRO 240 S neutralweiss schwarz****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss