

IS 3180 LiveLink - Unterputz eckig

neva
lux

Product code 4007841055752

- UV-resistant plastic

neva
lux

94 x 94 x 78 mm



IS 3180 LiveLink - Unterputz eckig

Product code 4007841055752

Technical Data

IDENTIFICATION	
Variant	LiveLink - concealed installation, square
Version	Motion detectors
DIMENSIONS	
Dimensions L x W x H	94 x 94 x 78 mm
ELECTRICAL	
Mains connection	230 V, 50 / 60 Hz
Supply voltage detail	DALI bus
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
Detection angle	180 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No

Tangential range	r = 8 m (101 m²) / r = 20 m (628 m²)
Switching zones	448 switching zones
Mounting height	1,50 – 3,00 m
Optimal mounting height	2 m
CONNECTIVITY	
Networking	Yes
Number of DALI participants	3
LIGHTING TECHNOLOGY	
Constant light regulation	No
SETTINGS	
Twilight setting	2 – 1000 lx
Time setting	5 sec – 15 min
Base light function	Yes
Settings via	LiveLink app

With remote control	No
Twilight setting teach	No
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	-20 – 50 °C
Mounting location	corner wall
Application location	Indoors Outdoors
Mounting type	Concealed wiring
Material	Plastic
RAL colour	9003
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
OTHER	
Application, location, room	corridor, aisle, stairwell, multi-storey car park, underground car park

IS 3180 LiveLink - Unterputz eckig

Product code 4007841055752

Illustrations

MOUNTING HEIGHT

1,50 – 3,00 m BEREICH	2 m OPTIMAL
--------------------------	----------------

IS 3180 LiveLink - Unterputz eckig

Product code 4007841055752

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841055752
Typ	IS 3180 LiveLink - Unterputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	