

XLED PRO Square XL SL schwarz



Product code 4007841010003

E-Nr. 924700251

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Interconnectable by cable

neva
lux

208 x 178 x 130 mm



XLED PRO Square XL SL schwarz

Product code **4007841010003**
E-Nr. **924700251**

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		SETTINGS	
Variant	black	Colour temperature	4000 K	Twilight switch	No
DIMENSIONS		LED colour deviation	SDCM3	Base light function time	10 min, 30 min, all night
Dimensions L x W x H	208 x 178 x 130 mm	Colour rendering index	80-89	HOUSING & MATERIAL	
ELECTRICAL		With illuminant	Yes, STEINEL LED system	Impact resistance	IK00
Mains connection	220 – 240 V , 50 / 60 Hz	Illuminant	LED cannot be replaced	Protection class (IP)	IP54
Power	48 W	LED cooling system	Passive Thermo Control	Protection class	I
SENSOR TECHNOLOGY		Continuous light	selectable, 4h	Ambient temperature	-20 – 40 °C
Max. mounting height	6,00 m	Luminous flux	4400 lm	Housing material	Aluminium
With motion detector	No	LIFETIME		Cover material	Plastic, transparent
		LED lifetime max. °C	50000 h	SCOPE OF DELIVERY & WARRANTY	
		Luminous flux decline per LM80	L70B10	Manufacturer warranty	5 years

XLED PRO Square XL SL schwarz

Product code **4007841010003**
E-Nr. **924700251**

Illustrations

MOUNTING HEIGHT



XLED PRO Square XL SL schwarz

Product code **4007841010003**
E-Nr. **924700251**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841007638	Fernbedienung RC9	Other

ORDERING INFORMATION

Art.-Nr.

4007841010003

E-Number

924700251

Typ

XLED PRO Square XL SL schwarz

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss