

L 170 S

neva
lux

Product code **4007841645311**

E-Nr. **924350279**

- Intelligent soft light start
- Optional basic lighting level 0 - 50 %
- High-quality designer trim panel in stainless steel
- 4-hour manual override (optional)

neva
lux

340 x 220 x 150 mm



L 170 S

Product code **4007841645311**
E-Nr. **924350279**

Technical Data

DIMENSIONS				SETTINGS	
Dimensions L x W x H	340 x 220 x 150 mm	Segment-by-segment masking	Yes	Twilight switch	Yes
ELECTRICAL		Electronic scalability	No	Twilight setting	2 – 2000 lx
Mains connection	230 – 240 V , 60 / 60 Hz	Mechanical scalability	No	Time setting	5 sec – 15 min
Power	100 W	Tangential range	r = 12 m (226 m²)	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY		Protection class (IP)	IP43
Sensor technology	passive infrared	With illuminant	No	Protection class	II
With motion detector	Yes	Illuminant	All-purpose lamp	Ambient temperature	-20 – 40 °C
Detection angle	180 °	Base	E27	Housing material	Stainless steel
Opening angle	90 °	Soft light start	Yes	Cover material	Glass transparent
Sneak-under protection	Yes	Continuous light	selectable, 4h	SCOPE OF DELIVERY & WARRANTY	
				Manufacturer warranty	3 years

L 170 S

Product code **4007841645311**
E-Nr. **924350279**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841001513	Ersatzglas für L 170 S	Coverage
 4007841002190	Ersatz-Grundkörper L 170 S / L 190 S	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841645311

E-Number

924350279

Typ

L 170 S

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss