

IR Quattro HD 24m DALI-2 APC - in-ceiling installation

neva
lux

PRESENCE DETECTOR

EAN 4007841079376

E-Nr. 535936908

 **steinel**

108 x 120 x 120 mm



IR Quattro HD 24m DALI-2 APC - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079376

E-Nr. 535936908

Technical Data

IDENTIFICATION	
Version	Presence detector
DIMENSIONS	
Dimensions L x W x H	108 x 120 x 120 mm
ELECTRICAL	
Mains connection	230 V / 50 – 60 Hz
Control output DALI	Broadcast 2x12 electronic ballasts
SENSOR TECHNOLOGY	
Max. mounting height	10,00 m
Sensor technology	passive infrared
Detection angle	360 °
Opening angle	160 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	No
Mechanical scalability	Yes
Radial range	8 x 8 m (64 m²)
Tangential range	20 x 20 m (400 m²)
Detection planes	13
Switching zones	4800 switching zones
Mounting height	2,50 – 10,00 m
Presence range	8 x 8 m (64 m²)

Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/slave
Networking via	Cable
With bus coupler	Yes
LIGHTING TECHNOLOGY	
Soft light start	Yes
Continuous light	selectable
Constant light regulation	Yes
SETTINGS	
Twilight switch	Yes
Twilight setting	10 – 1000 lx
Time setting	30 s – 30 Min.
Base light function	Yes
Base light function time	1-60 min, all night
Main light adjustable	50 - 100 %
Functions	Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF Constant-lighting control ON-OFF
Settings via	Remote control DIP switches Potentiometers Smart Remote

With remote control	No
Twilight setting teach	Yes
Base light function in percent	10 – 50 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	from -25 up to 55 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors changing room classroom conference room / meeting room duty room high-bay warehouse lecture hall multi-storey / underground car park open- plan office production facilities reception / lobby recreation room sports hall
Colour	white
RAL colour	9010
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro HD 24m DALI-2 APC - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079376
E-Nr. 535936908

Illustrations

TECHNICAL DRAWINGS



108 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------


IR Quattro HD 24m DALI-2 APC - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079376
E-Nr. 535936908


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave interconnection circuit diagram

IR Quattro HD 24m DALI-2 APC - in-ceiling installation

EAN 4007841079376

E-Nr. 535936908

PRESENCE DETECTOR


Highlights




4 pyros with DSP (Digital Signal Processing)



Optional remote controls



Optional surface-mounting adapter



Optional guard cage

IR Quattro HD 24m DALI-2 APC - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079376
E-Nr. 535936908

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

079376

EAN

4007841079376

E-Number

535936908

Typ

IR Quattro HD 24m DALI-2 APC - in-ceiling installation

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss