

DL Vario Quattro PRO S warmweiss silber

neva
lux

Product code **4007841035433**

E-Nr. **941300159**

- Including STEINEL LED system
- Integrated sensor lenses
- 4 infrared sensors adjustable in every direction
- Reach adjusts in 4 directions
- 4-hour manual override (optional)
- Impact-resistant material rated to IK07
- Interconnectable by cable (maximum of 10 units)

neva
lux

310 x 69 mm



DL Vario Quattro PRO S warmweiss silber

Product code 4007841035433
E-Nr. 941300159

Technical Data

DIMENSIONS					
Dimensions Ø x H	310 x 69 mm	Radial range	6 x 6 m (36 m²)	Base light function	Yes
ELECTRICAL		Tangential range	16 x 16 m (256 m²)	Base light function time	10/30 min, all night
Mains connection	220 – 240 V / 50 – 60 Hz	Mounting height	2,00 – 6,00 m	Settings via	Potentiometers
Power	14 W	Optimal mounting height	2,8 m	With remote control	No
Fluorescent lamps ECG	500 W	CONNECTIVITY		Twilight setting teach	No
Fluorescent lamps uncompensated	500 VA	Networking	Yes	Base light function in percent	10 %
Fluorescent lamps series-compensated	500 VA	Type of networking	Master/master	Base light function percent from	10 %
Fluorescent lamps parallel-compensated	500 VA	Networking via	Cable	HOUSING & MATERIAL	
Switching output 1 low-voltage halogen lamps	500 VA	Networking quantity	10 lights max.	Impact resistance	IK07
LED lamps < 2 W	16 W	Slave mode adjustable	No	Protection class (IP)	IP54
LED lamps > 2 W < 8 W	64 W	LIGHTING TECHNOLOGY		Protection class	II
LED lamps > 8 W	64 W	Measured luminous flux 360°	1430 lm	Ambient temperature	-20 – 35 °C
Capacitive load in µF	88 µF	Efficiency	102 lm/W	Housing material	Plastic
Own consumption	0,5 W	Colour temperature	3000 K	Cover material	Plastic, structured
SENSOR TECHNOLOGY		LED colour deviation	SDCM3	Mounting location	ceiling
Max. mounting height	6,00 m	Colour rendering index	80-89	Application location	Outdoors
Sensor technology	passive infrared	With illuminant	Yes, STEINEL LED system	Mounting type	Surface wiring
With motion detector	Yes	Illuminant	LED cannot be replaced	Material	Plastic
Detection angle	360 °	Base	without	Application room	Indoors corridor / aisle courtyard & driveway front door function room / ancillary room outdoors stairwell
Opening angle	180 °	LED cooling system	Passive Thermo Control	Colour	Silver
Sneak-under protection	Yes	Soft light start	Yes	SCOPE OF DELIVERY & WARRANTY	
Segment-by-segment masking	No	Continuous light	selectable, 4h	Manufacturer warranty	5 years
Electronic scalability	No	LIFETIME		CERTIFICATES & EPREL	
Mechanical scalability	Yes	LED lifetime max. °C	50000 h	Certificates	DEKRA\neMC
Range detail	Reach adjustable from 2 - 8 m in 4 directions (90° in each)	LED lifetime L70B50 25°C	> 60000 h	EPREL category	Surrounded product with integrated light source
		SETTINGS			
		Twilight switch	Yes		
		Twilight setting	2 – 1000 lx		
		Time setting	5 s – 30 Min.		

DL Vario Quattro PRO S warmweiss silber

Product code **4007841035433**
E-Nr. **941300159**

Illustrations

MOUNTING HEIGHT

2,00 – 6,00 m BEREICH	2,8 m OPTIMAL	6,00 m MAX
--------------------------	------------------	---------------

DL Vario Quattro PRO S warmweiss silber

Product code **4007841035433**E-Nr. **941300159**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841035433

E-Number 941300159

Typ **DL Vario Quattro PRO S warmweiss silber****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss