HF 360-2 KNX - concealed black

PRESENCE DETECTOR

EAN 4007841086749
E-Nr. 535903076

- Perfect radial detection with a range of up to 25 m, ideal for long corridors and hallways
- Customisable range that can be set individually in both directions
- Control PRO II design for a modern and functional look that enables versatile applications
- Bluetooth technology for simple connection and control via Bluetooth
- Multiple interfaces, compatible with COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD
- External light measurement required for black sensors that can be integrated via Bluetooth or KNX

steinel

60 x 103 x 103 mm



HF 360-2 KNX - concealed black

PRESENCE DETECTOR

EAN **4007841086749**
E-Nr. **535903076**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**60 x 103 x 103 mm**

ELECTRICAL

Mains connection	**30 V**
Supply voltage detail	**KNX bus**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 12 m (113 m²)**
Tangential range	**Ø 12 m (113 m²)**
Mounting height	**2,5 – 4 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
KNX functions	**Light output 4x Constant-lighting control Basic light level function Photo-cell controller Light level HVAC output Temperature output Humidity output Presence output Day / night function Dewpoint Comfort**
With bus coupler	**Yes**
Control technology	**Steinel Connect**
Wireless networking via	**BT SIG Mesh**
Networking via	**KNX**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**10 s – 1092 Min.**
Main light adjustable	**Yes**
Settings via	**Bluetooth Bus**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 50 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors WC / washroom function room / ancillary room kitchenette stairwell**
Colour	**black**
RAL colour	**9005**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


HF 360-2 KNX - concealed black

PRESENCE DETECTOR

EAN **4007841086749**
E-Nr. **535903076**

Illustrations

TECHNICAL DRAWINGS



60 x 103 x 103 mm

MOUNTING HEIGHT

2,5 – 4 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX

HF 360-2 KNX - concealed black

PRESENCE DETECTOR

EAN **4007841086749**
E-Nr. **535903076**

Highlights



UV-resistant plastic

HF 360-2 KNX - concealed black

PRESENCE DETECTOR

EAN **4007841086749**
E-Nr. **535903076**

Accessories

ORDERING INFORMATION

Art.-Nr.	086749
EAN	4007841086749
E-Number	535903076
Typ	**HF 360-2 KNX - concealed black**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss