

BLS

neva
lux

Product code **4007841720414**

E-Nr. **924360109**

- Multi-lens
- Shrouds

neva
lux

120 x 120 x 66 mm



Technical Data

IDENTIFICATION					
Version	Presence detector	Electronic scalability	No	Base light function	No
DIMENSIONS		Mechanical scalability	No	With remote control	No
Dimensions L x W x H	120 x 120 x 66 mm	Tangential range	Ø 24 m (452 m²)	Twilight setting teach	No
ELECTRICAL		Switching zones	1320 switching zones	HOUSING & MATERIAL	
Mains connection	230 – 240 V , 50 / 50 Hz	Mounting height	2,50 – 3,00 m	Protection class (IP)	IP20
Switching output 1 resistive	2000 W	Presence range	Ø 4 m (13 m²)	Ambient temperature	-20 – 50 °C
SENSOR TECHNOLOGY		Optimal mounting height	2,8 m	Mounting location	ceiling
Sensor technology	passive infrared	CONNECTIVITY		Application location	Indoors
Detection angle	360 °	Networking	Yes	Mounting type	Surface wiring
Opening angle	180 °	LIGHTING TECHNOLOGY		Material	Plastic
Sneak-under protection	Yes	Constant light regulation	No	Colour	white
Segment-by-segment masking	Yes	SETTINGS		RAL colour	9010
		Twilight setting	20 – 1300 lx	SCOPE OF DELIVERY & WARRANTY	
		Time setting	280 sec – 30 min	Manufacturer warranty	5 years

BLS

Product code **4007841720414**
E-Nr. **924360109**

Illustrations

MOUNTING HEIGHT

2,50 – 3,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

BLS

Product code **4007841720414**
E-Nr. **924360109**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841720414
E-Number	924360109
Typ	BLS
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	