

RS PRO 5850 LED Slave



Product code **4007841007683**

E-Nr. **941333979**

- Including STEINEL LED system
- Optional remote control
- Interconnectable via DALI, max. 15 slaves? / master
- Impact-resistant material rated to IK07
- Intelligent swarm function

neva
lux

1,583 x 105 x 105 mm



RS PRO 5850 LED Slave

Product code **4007841007683**
E-Nr. **941333979**

Technical Data

IDENTIFICATION		LED colour deviation		SDCM3	Twilight setting		2 – 2000 lx
Variant	Slave	Colour rendering index		80-89	Time setting		5 sec – 15 min
DIMENSIONS		With illuminant		Yes, STEINEL LED system	Functions		Group parameterisation, Neighbouring-light function, Presence function
Dimensions L x W x H	1,583 x 105 x 105 mm	Illuminant		LED cannot be replaced	HOUSING & MATERIAL		
ELECTRICAL		Base		without	Impact resistance		IK07
Mains connection	220 – 240 V , 50 / 60 Hz	LED cooling system		Passive Thermo Control	Protection class (IP)		IP66
Power	45 W	Soft light start		Yes	Protection class		I
SENSOR TECHNOLOGY		Luminous flux		5570 lm	Ambient temperature		-20 – 30 °C
Transmission power	< 1 mW	LIFETIME			Housing material		Plastic
With motion detector	No	LED lifetime max. °C		50000 h	Cover material		Plastic, opal
LIGHTING TECHNOLOGY		Luminous flux decline per LM80		L70B10	SCOPE OF DELIVERY & WARRANTY		
Colour temperature	4000 K	SETTINGS			Manufacturer warranty		5 years
		Twilight switch		No			

RS PRO 5850 LED Slave

Product code **4007841007683**
E-Nr. **941333979**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841008925	RC10 für RS PRO 5800/5850 LED	
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007683

E-Number

941333979

Typ

RS PRO 5850 LED Slave

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss