

# RS PRO Q1 S warmweiss weiss



Product code **4007841007133**

E-Nr. **941336009**

- Including STEINEL LED system
- Intelligent LED cooling system
- Intelligent soft light start
- Optional basic lighting level 10 - 50 %
- Wireless interconnection with Remote Group Setting
- High-quality aluminium
- Optional remote control RC10
- Smart Remote remote control optional

**neva**  
**lux**

56 x 331 x 331 mm



RS PRO Q1 S warmweiss weiss

Product code **4007841007133**  
E-Nr. **941336009**

Technical Data

| DIMENSIONS                              |  |  | LIGHTING TECHNOLOGY                                                                            |  |  | Settings via                     |  |  | DIP switches\nPotentiometers\nRemote control\nSmart Remote                                                         |  |  |
|-----------------------------------------|--|--|------------------------------------------------------------------------------------------------|--|--|----------------------------------|--|--|--------------------------------------------------------------------------------------------------------------------|--|--|
| Dimensions L x W x H                    |  |  | Measured luminous flux 360°                                                                    |  |  | With remote control              |  |  | No                                                                                                                 |  |  |
| 56 x 331 x 331 mm                       |  |  | Colour temperature                                                                             |  |  | Twilight setting teach           |  |  | Yes                                                                                                                |  |  |
| ELECTRICAL                              |  |  | LED colour deviation                                                                           |  |  | Base light function in percent   |  |  | 10 – 50 %                                                                                                          |  |  |
| Mains connection                        |  |  | With illuminant                                                                                |  |  | Base light function percent from |  |  | 10 %                                                                                                               |  |  |
| 220 – 240 V / 50 – 60 Hz                |  |  | Illuminant                                                                                     |  |  | HOUSING & MATERIAL               |  |  |                                                                                                                    |  |  |
| Power                                   |  |  | Base                                                                                           |  |  | Impact resistance                |  |  | IK03                                                                                                               |  |  |
| 26 W                                    |  |  | LED cooling system                                                                             |  |  | Protection class (IP)            |  |  | IP20                                                                                                               |  |  |
| SENSOR TECHNOLOGY                       |  |  | Soft light start                                                                               |  |  | Protection class                 |  |  | II                                                                                                                 |  |  |
| Max. mounting height                    |  |  | Continuous light                                                                               |  |  | Ambient temperature              |  |  | -10 – 50 °C                                                                                                        |  |  |
| 4,00 m                                  |  |  | LIFETIME                                                                                       |  |  | Housing material                 |  |  | Aluminium                                                                                                          |  |  |
| High frequency                          |  |  | LED lifetime max. °C                                                                           |  |  | Cover material                   |  |  | Plastic, opal                                                                                                      |  |  |
| Transmission power                      |  |  | LED lifetime L70B50 25°C                                                                       |  |  | Mounting location                |  |  | ceiling wall                                                                                                       |  |  |
| < 1 mW                                  |  |  | Luminous flux decline per LM80                                                                 |  |  | Application location             |  |  | Indoors                                                                                                            |  |  |
| 5,8 GHz                                 |  |  | SETTINGS                                                                                       |  |  | Mounting type                    |  |  | Surface wiring                                                                                                     |  |  |
| With motion detector                    |  |  | Twilight switch                                                                                |  |  | Application room                 |  |  | Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette outdoors stairwell |  |  |
| Yes                                     |  |  | Twilight setting                                                                               |  |  | Colour                           |  |  | white                                                                                                              |  |  |
| also through glass, wood and stud walls |  |  | Time setting                                                                                   |  |  | SCOPE OF DELIVERY & WARRANTY     |  |  |                                                                                                                    |  |  |
| Detection angle                         |  |  | Base light function                                                                            |  |  | Manufacturer warranty            |  |  | 5 years                                                                                                            |  |  |
| 360 °                                   |  |  | Base light function time                                                                       |  |  |                                  |  |  |                                                                                                                    |  |  |
| Opening angle                           |  |  | Main light adjustable                                                                          |  |  |                                  |  |  |                                                                                                                    |  |  |
| 160 °                                   |  |  | Functions                                                                                      |  |  |                                  |  |  |                                                                                                                    |  |  |
| Segment-by-segment masking              |  |  | Group parameterisation\nManual ON / ON-OFF\nMaster/slave override\nNeighbouring group function |  |  |                                  |  |  |                                                                                                                    |  |  |
| Yes                                     |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Electronic scalability                  |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Yes                                     |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Mechanical scalability                  |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| No                                      |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Radial range                            |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Ø 8 m (50 m²)                           |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Tangential range                        |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Ø 8 m (50 m²)                           |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Mounting height                         |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| 2,00 – 4,00 m                           |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Optimal mounting height                 |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| 2,5 m                                   |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| CONNECTIVITY                            |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Networking                              |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Yes                                     |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Type of networking                      |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Master/master\nMaster/slave             |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Networking via                          |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |
| Wireless                                |  |  |                                                                                                |  |  |                                  |  |  |                                                                                                                    |  |  |

RS PRO Q1 S warmweiss weiss

Product code **4007841007133**  
E-Nr. **941336009**

Illustrations

MOUNTING HEIGHT

|                          |                  |               |
|--------------------------|------------------|---------------|
| 2,00 – 4,00 m<br>BEREICH | 2,5 m<br>OPTIMAL | 4,00 m<br>MAX |
|--------------------------|------------------|---------------|

RS PRO Q1 S warmweiss weiss

Product code **4007841007133**  
E-Nr. **941336009**

Accessories

| ARTICLE NUMBER                                                                                  | DESCRIPTION        | CATEGORY  |
|-------------------------------------------------------------------------------------------------|--------------------|-----------|
|  4007841009151 | Smart Remote       | Accessory |
|  4007841007645 | RC10 für RS PRO Q1 | Accessory |

ORDERING INFORMATION

Art.-Nr.

4007841007133

E-Number

941336009

Typ

RS PRO Q1 S warmweiss weiss

neva  
lux

nevalux AG  
Neugrütstrasse 2  
8610 Uster  
+41 44 508 78 78  
info@nevalux.swiss