

elani P2400 3K

ELANI

neva
lux

Product code 221126

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

2400 x 60 x 80 mm



elani P2400 3K

ELANI

Product code 221126

Technical Data


DIMENSIONS		Colour rendering index		80-89		Constant light output control		No	
Dimensions L x W x H		2400 x 60 x 80 mm		Illuminant		Yes, LED-System			
Suspension length		2000 mm		Beam angle		Down 105°, Up 115°			
ELECTRICAL		Luminaire luminous efficacy		130 lm/W		HOUSING & MATERIAL		Protection class (IP)	
Mains connection		200...240 V / 50 – 60 Hz		Glare value		UGR < 22		IP20	
Power		74 W		LIFETIME		Protection class		II	
Replaceable driver		Yes		LED lifespan (25 °C)		70000 h		Ambient temperature	
Type of wiring		Suitable for through wiring		SETTINGS		DALI dimming		-20...45 °C	
SENSOR TECHNOLOGY		With motion detector		Yes		With emergency light		No	
With light sensor		No		Suitable for light band configuration		Yes		Housing material	
LIGHTING TECHNOLOGY		Colour temperature		3000 K		Direct/indirect ratio separately controllable		Yes	
LED colour deviation		SDCM3		CERTIFICATES & EPREL		EPREL energy efficiency class		D	

elani P2400 3K

ELANI

Product code 221126

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221396	elani Color RAL_NCS_2400	Other
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221126

Typ

elani P2400 3K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss