

zola C600 3CCT 10-20W



Product code **221564**

- Wide range of use in garages, basements, adjoining rooms, etc.
- 3 light colors selectable (3000, 4000 or 5700 Kelvin)
- Quick and easy mounting with separate mounting base
- Rear and side cable entry possible
- Wide beam diffuser (120 °)
- Version "Low Output" suitable for emergency lighting installations thanks to DC detection
- Available as emergency light version on request

neva
lux

603 x 71 x 64 mm



zola C600 3CCT 10-20W

Product code 221564

Technical Data

DIMENSIONS		Colour rendering index		80-89	HOUSING & MATERIAL		
Dimensions L x W x H		603 x 71 x 64 mm			Impact resistance		IK08
ELECTRICAL		Illuminant		LED	Protection class (IP)		IP20
Mains connection		200...240 V / 50 – 60 Hz			Protection class		I
Power		10 W (Default) / 13 W / 16 W / 20 W			Ambient temperature		-20...45 °C
Replaceable driver		Yes			Housing material		Steel
Type of wiring		Suitable for through wiring			Cover material		Diffusor opal
SENSOR TECHNOLOGY		Luminous flux		1100 lm (Default) / 1430 lm / 1760 lm / 2200 lm	Mounting type		Ceiling / wall surface-mounted
With motion detector		No			Colour		white
With light sensor		No			SCOPE OF DELIVERY & WARRANTY		
LIGHTING TECHNOLOGY		Beam angle		120°	Manufacturer warranty		5 years
Colour temperature		3000 / 4000 / 5700 K			CERTIFICATES & EPREL		
LED colour deviation		SDCM3			EPREL energy efficiency class		E
		LIFETIME					
		LED lifespan (25 °C)		50000 h			
		SETTINGS					
		DALI dimming		No			
		With emergency light		No			
		Suitable for light band configuration		Yes			

zola C600 3CCT 10-20W

Product code 221564

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221410	zola P-Set	Suspension cable

ORDERING INFORMATION

Art.-Nr.

221564

Typ

zola C600 3CCT 10-20W

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss