

RS PRO A30 SC Neutral white white

SENSOR-SWITCHED LED INDOOR LIGHT

neva
lux

EAN 4007841088347

E-Nr. 941600849

- Ideal for demanding environments such as pergolas or similar applications
- Non-visible high-frequency sensor with ø8 m range, 4000 K, 2745 lm, 20,7 W, 132,6 lm/W
- Robust aluminium housing with high impact resistance IK10 and protection class IP54
- Simple networking via Bluetooth Mesh Connect and commissioning via STEINEL Connect app
- Benefits of the Connected Lighting System and cross-range networking possible
- With plug-in terminals for easy installation

 **steinel**

331 x 69 mm



RS PRO A30 SC Neutral white white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841088347

E-Nr. 941600849

Technical Data

DIMENSIONS

Dimensions Ø x H	331 x 69 mm
------------------	-------------

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
------------------	--------------------------

Power	20,7 W
-------	--------

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
----------------------	--------

Sensor technology	High frequency
-------------------	----------------

Transmission power	< 1 mW
--------------------	--------

HF technology	5,8 GHz
---------------	---------

With motion detector	Yes
----------------------	-----

Detection	also through glass, wood and stud walls
-----------	---

Detection angle	360 °
-----------------	-------

Opening angle	160 °
---------------	-------

Segment-by-segment masking	No
----------------------------	----

Electronic scalability	Yes
------------------------	-----

Mechanical scalability	No
------------------------	----

Radial range	Ø 8 m (50 m²)
--------------	---------------

Tangential range	Ø 8 m (50 m²)
------------------	---------------

Mounting height	2,00 – 4,00 m
-----------------	---------------

Optimal mounting height	2,8 m
-------------------------	-------

CONNECTIVITY

Networking	Yes
------------	-----

Type of networking	Master/master
--------------------	---------------

Networking via	Bluetooth Mesh
----------------	----------------

Slave mode adjustable	Yes
-----------------------	-----

LIGHTING TECHNOLOGY

Measured luminous flux 360°	2745 lm
-----------------------------	---------

Colour temperature	4000 K
--------------------	--------

LED colour deviation	SDCM3
----------------------	-------

With illuminant	Yes, STEINEL LED system
-----------------	-------------------------

Illuminant	LED cannot be replaced
------------	------------------------

Base	without
------	---------

LED cooling system	Passive Thermo Control
--------------------	------------------------

Soft light start	Yes
------------------	-----

Continuous light	selectable
------------------	------------

Efficiency without cover	171,74 lm/W
--------------------------	-------------

LIFETIME

LED lifetime L70B50 25°C	> 60000 h
--------------------------	-----------

SETTINGS

Twilight switch	Yes
-----------------	-----

Twilight setting	2 – 2000 lx
------------------	-------------

Time setting	10 s – 60 Min.
--------------	----------------

Base light function	Yes
---------------------	-----

Base light function time	1-60 min
--------------------------	----------

Main light adjustable	0 - 100 %
-----------------------	-----------

Functions	Selecting programmed lighting scenarios Motions sensor DIM function Adjustable fade time when switching on and off Semi-/fully automatic Neighbouring group function Encrypted communication Timer
-----------	---

Settings via	Bluetooth App
--------------	---------------

With remote control	No
---------------------	----

Twilight setting teach	Yes
------------------------	-----

Base light function in percent	0 – 100 %
--------------------------------	-----------

Base light function percent from	0 %
----------------------------------	-----

HOUSING & MATERIAL

Impact resistance	IK10
-------------------	------

Protection class (IP)	IP54
-----------------------	------

Protection class	II
------------------	----

Ambient temperature	from -20 up to 40 °C
---------------------	----------------------

Housing material	Aluminium
------------------	-----------

Cover material	PC, opal
----------------	----------

Mounting location	ceiling wall
-------------------	--------------

Application location	Indoors
----------------------	---------

Mounting type	Surface wiring
---------------	----------------

Application room	WC / washroom changing room corridor / aisle function room / ancillary room kitchenette stairwell warehouse
------------------	---

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
-----------------------	---------

House number sheet included	No
-----------------------------	----

CERTIFICATES & EPREL

EPREL category	Surrounded product with integrated light source
----------------	---

RS PRO A30 SC Neutral white white


SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841088347

E-Nr. 941600849

Illustrations

TECHNICAL DRAWINGS



331 x 69 mm

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
---	-------------------------------------	----------------------------------

RS PRO A30 SC Neutral white white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841088347
E-Nr. 941600849

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221386	Universal P-Set 3S	Suspension cable

ORDERING INFORMATION

Art.-Nr.

088347

EAN

4007841088347

E-Number

941600849

Typ

RS PRO A30 SC Neutral white white

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss