

XSolar GL-S weiss



Product code **4007841671204**

E-Nr. **924808000**

- High-quality monocrystalline solar panel
- Including 2500 mAh lithium iron-phosphate rechargeable battery
- Including STEINEL LED system
- Optional basic lighting level
- Compass for setting the panel to face the optimum direction

neva
lux

188 x 194 x 1178 mm



XSolar GL-S weiss

Product code **4007841671204**
E-Nr. **924808000**

Technical Data

IDENTIFICATION					
Variant	white	Detection angle	140 °	Luminous flux decline per LM80	L70B10
DIMENSIONS		Sneak-under protection	Yes	SETTINGS	
Dimensions L x W x H	188 x 194 x 1178 mm	Tangential range	r = 5 m (31 m²)	Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Time setting	10 sec – 0,5 min
Power	1,2 W	Colour temperature	4000 K	HOUSING & MATERIAL	
Supply voltage detail	Solar supply, no mains power required, Lithium-iron-phosphate rechargeable battery 2500 mAh	LED colour deviation	SDCM5	Protection class (IP)	IP44
SENSOR TECHNOLOGY		Colour rendering index	80-89	Protection class	III
Sensor technology	passive infrared	With illuminant	Yes, STEINEL LED system	Housing material	Aluminium
With motion detector	Yes	Illuminant	LED cannot be replaced	Cover material	Plastic, transparent
		LED cooling system	Passive Thermo Control	SCOPE OF DELIVERY & WARRANTY	
		Luminous flux	150 lm	Manufacturer warranty	3 years
		LIFETIME			
		LED lifetime max. °C	50000 h		

XSolar GL-S weiss

Product code **4007841671204**E-Nr. **924808000**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841671204
----------	---------------

E-Number	924808000
----------	-----------

Typ	XSolar GL-S weiss
-----	--------------------------

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss