

nayo S 4K

neva
lux

Product code **220174**

- Glare-free optics with unreachd glare control UGR < 6
- Presence detector and constant light control
- Touchdim function with glass button
- Direct and indirect light proportion independently adjustable
- High luminaire efficiency with 130 lm/w
- Dimmable driver
- Housing Aluminium RAL9016, white

neva
lux

1053 x 64 x 1950 mm



nayo S 4K

Product code 220174

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	1053 x 64 x 1950 mm	LED colour deviation	SDCM3	Protection class (IP)	IP20
ELECTRICAL		Colour rendering index	80-89	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED	Ambient temperature	-20...45 °C
Power	80 W	Luminous flux	10400 lm (Down 3250, Up 7150)	Housing material	Aluminum
Replaceable driver	Yes	Beam angle	Down 50°, Up 110°	Cover material	Darklight Optics
SENSOR TECHNOLOGY		Luminaire luminous efficacy	130 lm/W	Mounting type	Free standing floor
Sensor technology	passive infrared	Glare value	UGR < 6	Colour	white
With motion detector	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
Presence range	Ø 3 m	SETTINGS		CERTIFICATES & EPREL	
With light sensor	Yes	Direct/indirect ratio separately controllable	Yes	EPREL energy efficiency class	D
LIGHTING TECHNOLOGY		With switch	Yes		
Colour temperature	4000 K				

nayo S 4K

Product code 220174

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220175	nayo P 4K	
 220463	nayo P Diffused 4K	

ORDERING INFORMATION

Art.-Nr.

220174

Typ

nayo S 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss