

# HF 3360 PF - Aufputz eckig

**neva**  
**lux**

Product code **4007841010546**

E-Nr. **535940467**

- UV-resistant plastic
- Large terminal compartment
- Optional corner wall mount bracket
- Optional remote controls

**neva**  
**lux**

52 x 95 x 95 mm



HF 3360 PF - Aufputz eckig

Product code **4007841010546**  
E-Nr. **535940467**

Technical Data

|                                              |                          |                            |                |                                         |                              |                                                                                                    |
|----------------------------------------------|--------------------------|----------------------------|----------------|-----------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------|
| IDENTIFICATION                               |                          | Detection                  |                | also through glass, wood and stud walls | Base light function          | No                                                                                                 |
| Version                                      | Motion detectors         | Detection angle            | 360 °          |                                         | Main light adjustable        | No                                                                                                 |
| DIMENSIONS                                   |                          | Opening angle              | 180 °          |                                         | Functions                    | Normal / test mode\nManual ON / ON-OFF                                                             |
| Dimensions L x W x H                         | 52 x 95 x 95 mm          | Sneak-under protection     | Yes            |                                         | Settings via                 | Remote control\nPotentiometers\nSmart Remote                                                       |
| ELECTRICAL                                   |                          | Segment-by-segment masking | No             |                                         | With remote control          | No                                                                                                 |
| Mains connection                             | 220 – 240 V / 50 – 60 Hz | Electronic scalability     | Yes            |                                         | Twilight setting teach       | Yes                                                                                                |
| Power                                        | 2000 W                   | Mechanical scalability     | No             |                                         | HOUSING & MATERIAL           |                                                                                                    |
| Fluorescent lamps ECG                        | 1500 W                   | Radial range               | Ø 8 m (50 m²)  |                                         | Protection class (IP)        | IP54                                                                                               |
| Fluorescent lamps uncompensated              | 1000 VA                  | Tangential range           | Ø 8 m (50 m²)  |                                         | Ambient temperature          | from -20 up to 50 °C                                                                               |
| Fluorescent lamps series-compensated         | 400 VA                   | Mounting height            | 2,00 – 4,00 m  |                                         | Mounting location            | ceiling corner wall                                                                                |
| Fluorescent lamps parallel-compensated       | 400 VA                   | Optimal mounting height    | 2,8 m          |                                         | Application location         | Indoors                                                                                            |
| Switching output 1 low-voltage halogen lamps | 2000 VA                  | CONNECTIVITY               |                |                                         | Mounting type                | Surface wiring                                                                                     |
| LED lamps < 2 W                              | 100 W                    | Networking                 | Yes            |                                         | Material                     | Plastic                                                                                            |
| LED lamps > 2 W < 8 W                        | 300 W                    | Type of networking         | Master/master  |                                         | Application room             | Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell |
| LED lamps > 8 W                              | 600 W                    | Networking via             | Cable          |                                         | Colour                       | white                                                                                              |
| Capacitive load in µF                        | 176 µF                   | LIGHTING TECHNOLOGY        |                |                                         | RAL colour                   | 9003                                                                                               |
| SENSOR TECHNOLOGY                            |                          | Soft light start           | No             |                                         | SCOPE OF DELIVERY & WARRANTY |                                                                                                    |
| Max. mounting height                         | 4,00 m                   | Continuous light           | selectable, 4h |                                         | Manufacturer warranty        | 5 years                                                                                            |
| Sensor technology                            | High frequency           | Constant light regulation  | No             |                                         | Corner wall bracket included | No                                                                                                 |
| Transmission power                           | < 1 mW                   | SETTINGS                   |                |                                         |                              |                                                                                                    |
| HF technology                                | 5,8 GHz                  | Twilight switch            | Yes            |                                         |                              |                                                                                                    |
|                                              |                          | Twilight setting           | 2 – 1000 lx    |                                         |                              |                                                                                                    |
|                                              |                          | Time setting               | 5 s – 15 Min.  |                                         |                              |                                                                                                    |

HF 3360 PF - Aufputz eckig

Product code **4007841010546**  
E-Nr. **535940467**

Illustrations

MOUNTING HEIGHT

|                          |                  |               |
|--------------------------|------------------|---------------|
| 2,00 – 4,00 m<br>BEREICH | 2,8 m<br>OPTIMAL | 4,00 m<br>MAX |
|--------------------------|------------------|---------------|

HF 3360 PF - Aufputz eckig

Product code **4007841010546**  
E-Nr. **535940467**

Accessories

| ARTICLE NUMBER                                                                                   | DESCRIPTION                                   | CATEGORY       |
|--------------------------------------------------------------------------------------------------|-----------------------------------------------|----------------|
|  4007841009151  | Smart Remote                                  | Accessory      |
|  4007841559410  | Service Fernbedienung RC8                     | Accessory      |
|  4007841035174   | Eckwandhalter 3000 weiss                      | Corner adapter |
|  4007841056674  | Schwarze Blende für den HF 3360 Aufputz eckig | Coverage       |
|  4007841056698 | Schwarze Blende für den HF 3360 Aufputz rund  | Coverage       |

ORDERING INFORMATION

Art.-Nr.

4007841010546

E-Number

535940467

Typ

HF 3360 PF - Aufputz eckig

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss