

IS 3360 PF - concealed, rd.

MOTION AND PRESENCE DETECTOR

neva
lux

EAN 4007841033484

E-Nr. 535946307

● steinel

124 x 78 mm



IS 3360 PF - concealed, rd.

MOTION AND PRESENCE DETECTOR

EAN 4007841033484
E-Nr. 535946307

Technical Data

IDENTIFICATION

Version	Motion and Presence Detector
---------	------------------------------

DIMENSIONS

Dimensions Ø x H	124 x 78 mm
------------------	-------------

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	400 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in µF	176 µF

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360 °

Opening angle	180 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 40 m (1257 m²)
Switching zones	1416 switching zones
Mounting height	2,50 – 4,00 m
Presence range	Ø 3 m (7 m²)
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master
Networking via	Cable

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable, 4h
Constant light regulation	No

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 Min.
Base light function	No

Main light adjustable	No
Functions	Normal / test mode Manual ON / ON-OFF
Settings via	Remote control Potentiometers Smart Remote
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors WC / washroom changing room function room / ancillary room multi-storey / underground car park production facilities reception / lobby recreation room sports hall stairwell warehouse

Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY


Manufacturer warranty	5 years
Corner wall bracket included	No

IS 3360 PF - concealed, rd.
MOTION AND PRESENCE DETECTOR

EAN 4007841033484
E-Nr. 535946307

Illustrations

TECHNICAL DRAWINGS



124 x 78 mm

MOUNTING HEIGHT

2,50 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

IS 3360 PF - concealed, rd.


MOTION AND PRESENCE DETECTOR

EAN 4007841033484

E-Nr. 535946307

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

IS 3360 PF - concealed, rd.

MOTION AND PRESENCE DETECTOR

EAN 4007841033484

E-Nr. 535946307

Highlights



UV-resistant plastic




Optional remote controls

IS 3360 PF - concealed, rd.
MOTION AND PRESENCE DETECTOR

EAN 4007841033484
E-Nr. 535946307

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841056728	Schwarze Blende für IR-Sensoren Unterputz eckig	Accessory
 4007841056742	Schwarze Blende für IR-Sensoren Unterputz rund	Accessory
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

033484

EAN

4007841033484

E-Number

535946307

Typ

IS 3360 PF - concealed, rd.

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss