IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002756
E-Nr. 535933905

steinel

70 x 120 x 120 mm



IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841002756**
E-Nr. **535933905**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**70 x 120 x 120 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Control output DALI	**Broadcast 2x12 electronic ballasts**

SENSOR TECHNOLOGY

Max. mounting height	**10,00 m**
Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**160 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**No**
Mechanical scalability	**Yes**
Radial range	**8 x 8 m (64 m²)**
Tangential range	**20 x 20 m (400 m²)**
Detection planes	**13**
Switching zones	**4800 switching zones**
Mounting height	**2,50 – 10,00 m**
Presence range	**8 x 8 m (64 m²)**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/slave**
Networking via	**DALI 2**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**30 s – 30 Min.**
Base light function	**Yes**
Base light function time	**1-60 min, all night**
Main light adjustable	**50 - 100 %**
Functions	**Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF Constant-lighting control ON-OFF**
Settings via	**Remote control DIP switches Potentiometers Smart Remote**
With remote control	**No**
Twilight setting teach	**Yes**
Base light function in percent	**10 – 50 %**
Base light function percent from	**10 %**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors changing room classroom conference room / meeting room duty room high-bay warehouse lecture hall multi-storey / underground car park open-plan office production facilities reception / lobby recreation room sports hall**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**

CERTIFICATES & EPREL

Certificates	**DALI-2**


IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841002756**
E-Nr. **535933905**

Illustrations

TECHNICAL DRAWINGS



70 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 10,00 m	2,8 m	10,00 m
BEREICH	OPTIMAL	MAX


IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002756
E-Nr. 535933905


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002756
E-Nr. 535933905


Highlights




4 pyros with DSP (Digital Signal Processing)



Optional remote controls



Optional surface-mounting adapter



Optional guard cage

IR Quattro HD 24m DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002756
E-Nr. 535933905

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841592806	**Nutzer Fernbedienung RC5**	Accessory
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	002756
EAN	4007841002756
E-Number	535933905
Typ	**IR Quattro HD 24m DALI-2 APC - concealed**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss