

elani C1500 4K

ELANI

neva
lux

Product code **221130**

- For universal use for lighting offices, schools, traffic zones etc.
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

1500 x 60 x 80 mm



elani C1500 4K

ELANI

Product code 221130

Technical Data

DIMENSIONS		Colour rendering index		80-89	HOUSING & MATERIAL	
Dimensions L x W x H	1500 x 60 x 80 mm	Illuminant	Yes, LED-System		Protection class (IP)	IP20
ELECTRICAL		Luminous flux	4200 lm		Protection class	II
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	105°		Ambient temperature	-20...45 °C
Power	37,5 W	Luminaire luminous efficacy	112 lm/W		Housing material	Aluminium
Replaceable driver	Yes	Glare value	UGR < 24		Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	LIFETIME		Mounting type		Ceiling / wall surface-mounted
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h		Colour	Aluminium
With motion detector	No	SETTINGS		SCOPE OF DELIVERY & WARRANTY		
With light sensor	No	DALI dimming	Yes		Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		With emergency light	No		CERTIFICATES & EPREL	
Colour temperature	4000 K	Suitable for light band configuration	Yes		EPREL energy efficiency class	E
LED colour deviation	SDCM3					

elani C1500 4K

ELANI

Product code 221130

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221100	elani Diffusor 1500 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221106	elani Color RAL_NCS_1500	Other
 221107	elani Link	Coupler/connector straight
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221130

Typ

elani C1500 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss