Dual US COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079598
E-Nr. 535930110

steinel

109 x 120 x 120 mm



Dual US COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079598**
E-Nr. **535930110**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**109 x 120 x 120 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**

SENSOR TECHNOLOGY

Max. mounting height	**3,50 m**
Sensor technology	**Ultrasonic**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**20 x 3 m (60 m²)**
Tangential range	**20 x 3 m (60 m²)**
Mounting height	**2,50 – 3,50 m**
US technology	**40 kHz**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
Networking quantity	**max. 10 sensors**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**30 s – 30 Min.**
Base light function	**No**
Main light adjustable	**No**
Functions	**Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF**
Settings via	**Remote control DIP switches Potentiometers Smart Remote**
With remote control	**Yes**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**In-ceiling installation**
Material	**Plastic**
Application room	**Indoors corridor / aisle**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


Dual US COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079598**
E-Nr. **535930110**

Illustrations

TECHNICAL DRAWINGS



109 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,50 m	2,8 m	3,50 m
BEREICH	OPTIMAL	MAX


Dual US COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079598**
E-Nr. **535930110**


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

Dual US COM1 - in-ceiling installation


PRESENCE DETECTOR

EAN 4007841079598
E-Nr. 535930110


Highlights



Optional remote controls



Optional surface-mounting adapter



Optional guard cage

Dual US COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079598**
E-Nr. **535930110**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	079598
EAN	4007841079598
E-Number	535930110
Typ	**Dual US COM1 - in-ceiling installation**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss