

RS PRO Q1 S neutralweiss weiss



Product code **4007841007119**

E-Nr. **941336109**

- Including STEINEL LED system
- Intelligent LED cooling system
- Intelligent soft light start
- Optional basic lighting level 10 - 50 %
- Wireless interconnection with Remote Group Setting
- High-quality aluminium
- Optional remote control RC10
- Smart Remote remote control optional

neva
lux

56 x 331 x 331 mm



RS PRO Q1 S neutralweiss weiss

Product code **4007841007119**
E-Nr. **941336109**

Technical Data

DIMENSIONS			LIGHTING TECHNOLOGY			Settings via			DIP switches\nPotentiometers\nRemote control\nSmart Remote		
Dimensions L x W x H			Measured luminous flux 360°			With remote control			No		
56 x 331 x 331 mm			Colour temperature			Twilight setting teach			Yes		
ELECTRICAL			LED colour deviation			Base light function in percent			10 – 50 %		
Mains connection			With illuminant			Base light function percent from			10 %		
220 – 240 V / 50 – 60 Hz			Illuminant			HOUSING & MATERIAL					
Power			Base			Impact resistance			IK03		
26 W			LED cooling system			Protection class (IP)			IP20		
SENSOR TECHNOLOGY			Soft light start			Protection class			II		
Max. mounting height			Continuous light			Ambient temperature			-10 – 50 °C		
4,00 m			LIFETIME			Housing material			Aluminium		
High frequency			LED lifetime max. °C			Cover material			Plastic, opal		
Transmission power			LED lifetime L70B50 25°C			Mounting location			ceiling wall		
< 1 mW			Luminous flux decline per LM80			Application location			Indoors		
5,8 GHz			SETTINGS			Mounting type			Surface wiring		
Yes			Twilight switch			Application room			Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette outdoors stairwell		
also through glass, wood and stud walls			Twilight setting			Colour			white		
Detection angle			Time setting			SCOPE OF DELIVERY & WARRANTY					
360 °			Base light function			Manufacturer warranty			5 years		
Opening angle			Base light function time								
160 °			Main light adjustable								
Segment-by-segment masking			Functions								
Yes			Group parameterisation\nManual ON / ON-OFF\nMaster/slave override\nNeighbouring group function								
Electronic scalability											
Yes											
Mechanical scalability											
No											
Radial range											
Ø 8 m (50 m²)											
Tangential range											
Ø 8 m (50 m²)											
Mounting height											
2,00 – 4,00 m											
Optimal mounting height											
2,5 m											
CONNECTIVITY											
Networking											
Yes											
Type of networking											
Master/master\nMaster/slave											
Networking via											
Wireless											

RS PRO Q1 S neutralweiss weiss

Product code **4007841007119**
E-Nr. **941336109**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,5 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

RS PRO Q1 S neutralweiss weiss

Product code **4007841007119**
E-Nr. **941336109**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841007645	RC10 für RS PRO Q1	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007119

E-Number

941336109

Typ

RS PRO Q1 S neutralweiss weiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss