

elani C1500 TW

ELANI

neva
lux

Product code **221132**

- For universal use for lighting offices, schools, traffic zones etc.
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

1500 x 60 x 80 mm



elani C1500 TW

ELANI

Product code 221132

Technical Data



DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	1500 x 60 x 80 mm	Colour rendering index	80-89	Protection class (IP)	IP20
ELECTRICAL		Illuminant	Yes, LED-System	Protection class	II
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	4200 lm	Ambient temperature	-20...45 °C
Power	37,5 W	Beam angle	105°	Housing material	Aluminium
Replaceable driver	Yes	Luminaire luminous efficacy	112 lm/W	Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	Glare value	UGR < 24	Mounting type	Ceiling / wall surface-mounted
SENSOR TECHNOLOGY		LIFETIME		Colour	Aluminium
With motion detector	No	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	SETTINGS		Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		DALI dimming	Yes	CERTIFICATES & EPREL	
Colour temperature	3000...5600 K	With emergency light	No	EPREL energy efficiency class	E
LED colour deviation	SDCM3	Suitable for light band configuration	Yes		

elani C1500 TW

ELANI

Product code 221132

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221100	elani Diffusor 1500 CDP	Cover
 221343	elani Connector 90°	Coupler/connector L-shape
 221106	elani Color RAL_NCS_1500	Other
 221107	elani Link	Coupler/connector straight
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221132

Typ

elani C1500 TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss