Spot Way SC with motion detector & Bluetooth

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841058661
E-Nr. 941200469

- Floor and path luminaire with motion detector, perfect for illuminating paths and driveways
- Elegant and puristic design made of high-quality aluminium, spotlight head can be swivelled 180° horizontally and 90° vertically
- Wireless networking via Bluetooth and easy setting via STEINEL Connect App
- Automatic light thanks to 90° Infrared sensor with up to 10 m detection of movement
- Functions: Twilight-controlled light, integrated timer, night economy mode, 4 hours continuous light
- Incl. GU-10 LED bulb with warm white light (3000 K) with 512 lm at 7,9 W
- Incl. 2.5 m mains cable and mounting accessories - plastic-free packaging

steinel

226 x 140 x 572 mm



Spot Way SC with motion detector & Bluetooth

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841058661**
E-Nr. **941200469**

Technical Data

DIMENSIONS

Dimensions L × W × H	**226 x 140 x 572 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**7,9 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**90 °**
Opening angle	**90 °**
Sneak-under protection	**No**
Segment-by-segment masking	**No**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 2 m (3 m²)**
Tangential range	**r = 10 m (79 m²)**

CONNECTIVITY

Networking	**Yes**
Slave mode adjustable	**Yes**
Control technology	**Steinel Connect**

LIGHTING TECHNOLOGY

Measured luminous flux 360°	**512 lm**
Colour temperature	**3000 K**
LED colour deviation	**SDCM5**
Colour rendering index	**80-89**
With illuminant	**Yes, LED lamp**
Illuminant	**LED can be replaced**
Base	**GU10**
Soft light start	**No**
Continuous light	**selectable, 4h**

LIFETIME

LED lifetime L70B50 25°C	**> 20000 h**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 60 Min.**
Base light function	**No**
Main light adjustable	**No**
Functions	**Manual ON / ON-OFF Timer Master/slave override**
Settings via	**Bluetooth**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Impact resistance	**IK03**
Protection class (IP)	**IP44**
Protection class	**I**
Ambient temperature	**from -20 up to 40 °C**
Housing material	**Aluminium**
Cover material	**Plastic, transparent**
Mounting location	**Stand mounted**
Application location	**Outdoors**
Mounting type	**Surface wiring**
Application room	**garden outdoors**
Colour	**Anthracite**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**
Corner wall bracket included	**No**

CERTIFICATES & EPREL

EPREL energy efficiency class	**F**
EPREL category	**Surrounded product with separate light source (e.g. E27)**


Spot Way SC with motion detector & Bluetooth

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841058661**
E-Nr. **941200469**

Illustrations

TECHNICAL DRAWINGS



226 x 140 x 572 mm

Spot Way SC with motion detector & Bluetooth

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841058661**
E-Nr. **941200469**


Highlights



Including GU10 LED lamp




LED ambient light



High-quality aluminium



Turns through 180° and tilts through 90°



With 2.5m mains connection cable



4-hour manual override (optional)

Spot Way SC with motion detector & Bluetooth

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841058661**
E-Nr. **941200469**

Accessories

ORDERING INFORMATION

Art.-Nr.	058661
EAN	4007841058661
E-Number	941200469
Typ	**Spot Way SC with motion detector & Bluetooth**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss