

XLED PRO 240 anthrazit

neva
lux

Product code **4007841057695**

E-Nr. **924702412**

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80
- Including corner wall mount

neva
lux

221 x 180 x 161 mm



XLED PRO 240 anthrazit

Product code **4007841057695**
E-Nr. **924702412**

Technical Data

IDENTIFICATION			
Variant	Anthracite	Sneak-under protection	Yes
DIMENSIONS		Segment-by-segment masking	Yes
Dimensions L x W x H	221 x 180 x 161 mm	Tangential range	r = 12 m (302 m²)
ELECTRICAL		LIGHTING TECHNOLOGY	
Mains connection	230 – 240 V	Colour temperature	4000 K
Power	20 W	LED colour deviation	SDCM3
SENSOR TECHNOLOGY		Colour rendering index	80-89
Max. mounting height	6,00 m	With illuminant	Yes, STEINEL LED system
Sensor technology	passive infrared	Illuminant	LED cannot be replaced
With motion detector	Yes	Luminous flux	1830 lm
Detection angle	240 °	LIFETIME	
Opening angle	180 °	LED lifetime max. °C	60000 h
		Luminous flux decline per LM80	
		L70B10	
		SETTINGS	
		Twilight switch	Yes
		HOUSING & MATERIAL	
		Impact resistance	IK00
		Protection class (IP)	IP44
		Protection class	II
		Housing material	Plastic
		Cover material	Plastic, opal
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		Corner wall bracket included	Yes

XLED PRO 240 anthrazit

Product code **4007841057695**
E-Nr. **924702412**

Illustrations

MOUNTING HEIGHT



XLED PRO 240 anthrazit

Product code **4007841057695**
E-Nr. **924702412**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841057701	XLED PRO 240 SL anthrazit	

ORDERING INFORMATION

Art.-Nr.

4007841057695

E-Number

924702412

Typ

XLED PRO 240 anthrazit

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss