

RS LED M1 Chrom

neva
lux

Product code **4007841052485**

E-Nr. **941301179**

- Including STEINEL LED system
- LED ambient light
- 4-hour manual override (optional)
- Optional basic lighting level 10 %
- High-quality materials

neva
lux

200 x 200 x 53 mm



RS LED M1 Chrom

Product code **4007841052485**
E-Nr. **941301179**

Technical Data

IDENTIFICATION		CONNECTIVITY		SETTINGS	
Variant	Chrome	Networking	Yes	Twilight switch	Yes
DIMENSIONS		LIGHTING TECHNOLOGY		Twilight setting	2 – 2000 lx
Dimensions L x W x H	200 x 200 x 53 mm	Colour temperature	3000 K	Time setting	5 sec – 15 min
ELECTRICAL		LED colour deviation	SDCM3	Base light function	Yes
Mains connection	220 – 240 V , 50 / 60 Hz	Colour rendering index	80-89	Base light function time	10/30 min, all night
Power	9,5 W	With illuminant	Yes, STEINEL LED system	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		Illuminant	LED cannot be replaced	Impact resistance	IK00
Sensor technology	High frequency	Base	without	Protection class (IP)	IP20
Transmission power	< 1 mW	LED cooling system	Passive Thermo Control	Protection class	II
With motion detector	Yes	Soft light start	Yes	Ambient temperature	-10 – 30 °C
Detection	also through glass, wood and stud walls	Continuous light	selectable, 4h	Housing material	Plastic
Detection angle	360 °	Luminous flux	560 lm	Cover material	Plastic, opal
Opening angle	160 °	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Electronic scalability	Yes	LED lifetime max. °C	65000 h	Manufacturer warranty	3 years
Mechanical scalability	No	Luminous flux decline per LM80	L70B10		

RS LED M1 Chrom

Product code **4007841052485**
E-Nr. **941301179**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841052485
E-Number	941301179
Typ	RS LED M1 Chrom

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss