

L 244 LED Edelstahl

neva
lux

Product code **4007841033255**

- Including STEINEL LED system
- LED ambient light
- Rustproof stainless steel trim
- Impact-resistant material rated to IK07

neva
lux

305 x 165 x 81 mm



L 244 LED Edelstahl

Product code 4007841033255

Technical Data

IDENTIFICATION					
Variant	Stainless steel	Mechanical scalability	No	Luminous flux decline per LM80	L70B10
DIMENSIONS		Radial range	r = 3 m (14 m²)	SETTINGS	
Dimensions L x W x H	305 x 165 x 81 mm	Tangential range	r = 10 m (157 m²)	Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Twilight setting	2 – 2000 lx
Mains connection	220 – 240 V , 50 / 60 Hz	Colour temperature	3000 K	Time setting	8 sec – 35 min
Power	7,5 W	LED colour deviation	SDCM3	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		Colour rendering index	80-89	Impact resistance	IK07
Sensor technology	passive infrared	With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP44
With motion detector	Yes	Illuminant	LED cannot be replaced	Protection class	II
Detection angle	180 °	Base	without	Ambient temperature	-20 – 50 °C
Sneak-under protection	Yes	LED cooling system	Passive Thermo Control	Housing material	Stainless steel
Segment-by-segment masking	Yes	Luminous flux	500 lm	Cover material	Plastic, opal
		LIFETIME		SCOPE OF DELIVERY & WARRANTY	
		LED lifetime max. °C	50000 h	Manufacturer warranty	3 years

L 244 LED Edelstahl

Product code **4007841033255**

Accessories

ORDERING INFORMATION

Art.-Nr. **4007841033255**

Typ **L 244 LED Edelstahl**

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss