

XLED PRO 240 schwarz

neva
lux

Product code **4007841003623**

E-Nr. **924702411**

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80
- Including corner wall mount

neva
lux

221 x 180 x 161 mm



XLED PRO 240 schwarz

Product code **4007841003623**
E-Nr. **924702411**

Technical Data

IDENTIFICATION				SETTINGS	
Variant	black	Segment-by-segment masking	Yes	Twilight switch	Yes
DIMENSIONS		Tangential range	r = 12 m (302 m²)	Twilight setting	2 – 1000 lx
Dimensions L x W x H	221 x 180 x 161 mm	LIGHTING TECHNOLOGY		Time setting	10 sec – 15 min
ELECTRICAL		Colour temperature	4000 K	HOUSING & MATERIAL	
Mains connection	230 – 240 V , 50 / 60 Hz	LED colour deviation	SDCM3	Impact resistance	IK00
Power	20 W	Colour rendering index	80-89	Protection class (IP)	IP44
SENSOR TECHNOLOGY		With illuminant	Yes, STEINEL LED system	Protection class	II
Max. mounting height	6,00 m	Illuminant	LED cannot be replaced	Housing material	HCMC
Sensor technology	passive infrared	LED cooling system	HCMC (High Conductive Magnesium Composite)	Cover material	Plastic, opal
With motion detector	Yes	Luminous flux	1830 lm	SCOPE OF DELIVERY & WARRANTY	
Detection angle	240 °	LIFETIME		Manufacturer warranty	5 years
Opening angle	180 °	LED lifetime max. °C	60000 h	Corner wall bracket included	Yes
Sneak-under protection	Yes	Luminous flux decline per LM80	L70B10		

XLED PRO 240 schwarz

Product code **4007841003623**
E-Nr. **924702411**

Illustrations

MOUNTING HEIGHT



XLED PRO 240 schwarz

Product code **4007841003623**
E-Nr. **924702411**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841057718	XLED PRO 240 SL schwarz	

ORDERING INFORMATION

Art.-Nr.

4007841003623

E-Number

924702411

Typ

XLED PRO 240 schwarz

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss