

RS PRO Connect 5100 LED Sensor Verso



Product code **220482**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Optional basic lighting level 10 - 50 %
- Optional basic light level 50 - 100%
- Adjustable mounts for easy installation

neva
lux

1,370 x 87 x 58 mm



RS PRO Connect 5100 LED Sensor Verso

Product code 220482

Technical Data

IDENTIFICATION	
Variant	Sensor Verso
DIMENSIONS	
Dimensions L x W x H	1,370 x 87 x 58 mm
ELECTRICAL	
Mains connection	220 – 240 V , 50 / 60 Hz
Power	30 W
SENSOR TECHNOLOGY	
Sensor technology	High frequency
Transmission power	< 1 mW
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Electronic scalability	Yes
Mechanical scalability	No
CONNECTIVITY	
Networking	Yes
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
LED cooling system	Passive Thermo Control
Luminous flux	4200 lm
LIFETIME	
LED lifetime max. °C	60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 60 min
Base light function	Yes
Base light function time	10-30 min, all night
Functions	Neighbouring-light function, Presence function, Group parameterisation
Settings via	Bluetooth
With remote control	Yes
HOUSING & MATERIAL	
Impact resistance	IK07
Protection class (IP)	IP40
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, structured
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years

RS PRO Connect 5100 LED Sensor Verso

Product code 220482

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841052904	RS PRO 5100 C Slave	

ORDERING INFORMATION

Art.-Nr.

220482

Typ

RS PRO Connect 5100 LED Sensor Verso

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss