IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN 4007841064334
E-Nr. 535939600

- Passive infrared presence detector with square 360° detection
- 5.200 switching zones for the finest detection
- Offers the largest detection range in our IR range
- 4 pyro sensors individually de- / activatable
- Sensitivity digitally adjustable
- Measures presence and brightness
- Temperature and humidity measurement with IP, KNX and DALI-2 IPD
- Setting and networking via Bluetooth
- Ideal for open-plan offices and classrooms

steinel

69 x 103 x 103 mm



IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN 4007841064334
E-Nr. 535939600

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	69 x 103 x 103 mm

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	1000 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in µF	176 µF
Own consumption	0,3 W
Switching output 1 number of LED/fluorescent lamps	8 pcs.
Switching output 1 potential-free	No
Switching output 2 resistive	230 W
Switching output 2 potential-free	Yes

SENSOR TECHNOLOGY

Max. mounting height	10,00 m
Sensor technology	passive infrared
Detection angle	360 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	Yes
Radial range	9 x 9 m (81 m²)
Tangential range	24 x 24 m (576 m²)
Switching zones	5200 switching zones
Mounting height	2,50 – 10,00 m
Presence range	9 x 9 m (81 m²)
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Control technology	Steinel Connect
Wireless networking via	BT SIG Mesh

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Group parameterisation Semi-/fully automatic Lighting scenario Manual ON / ON-OFF Neighbouring group function Normal / test mode
Settings via	Bluetooth Mesh App Potentiometers Smartphone
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors changing room classroom conference room / meeting room dining hall / staff restaurant duty room high-bay warehouse lecture hall multi-storey / underground car park open-plan office production facilities reception / lobby recreation room sports hall
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064334**
E-Nr. **535939600**

Illustrations

TECHNICAL DRAWINGS



69 x 103 x 103 mm

MOUNTING HEIGHT

2,50 – 10,00 m	2,8 m	10,00 m
BEREICH	OPTIMAL	MAX


IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN 4007841064334
E-Nr. 535939600

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN 4007841064334
E-Nr. 535939600

Highlights



UV-resistant plastic

IR Quattro HD-2 24m COM2 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064334**
E-Nr. **535939600**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841067335	**Relais REL5A-Bluetooth**	System components
	4007841067342	**Tasterkoppler PC4-Bluetooth**	System components

ORDERING INFORMATION

Art.-Nr.	064334
EAN	4007841064334
E-Number	535939600
Typ	**IR Quattro HD-2 24m COM2 - Concealed wiring**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss