

RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

neva
lux**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN 4007841068431

E-Nr. 941349329

 **steinel**

300 x 55 mm



RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841068431
E-Nr. 941349329

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		Settings via	Bluetooth
Dimensions Ø x H	300 x 55 mm	Measured luminous flux 360°	992 lm	With remote control	No
ELECTRICAL		Colour temperature	3000 K	Twilight setting teach	Yes
Mains connection	220 – 240 V / 50 – 60 Hz	LED colour deviation	SDCM3	Base light function in percent	0 – 100 %
Power	8,5 W	With illuminant	Yes, STEINEL LED system	Base light function percent from	0 %
Own consumption	0,3 W	Illuminant	LED cannot be replaced	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		Base	without	Impact resistance	IK07
Max. mounting height	4,00 m	LED cooling system	Passive Thermo Control	Protection class (IP)	IP40
Sensor technology	High frequency	Soft light start	Yes	Protection class	II
Transmission power	< 1 mW	Continuous light	selectable	Ambient temperature	from -20 up to 40 °C
HF technology	5,8 GHz	LIFETIME		Housing material	Plastic
With motion detector	Yes	LED lifetime max. °C	55000 h	Cover material	PC, opal
Detection	also through glass, wood and stud walls	LED lifetime L70B50 25°C	> 60000 h	Mounting location	ceiling wall
Detection angle	360 °	Luminous flux decline per LM80	L80B50	Application location	Indoors
Opening angle	160 °	SETTINGS		Mounting type	Surface wiring
Segment-by-segment masking	Yes	Twilight switch	Yes	Material	Plastic
Electronic scalability	Yes	Twilight setting	2 – 2000 lx	Application room	Indoors changing room corridor / aisle function room / ancillary room kitchenette stairwell
Mechanical scalability	No	Time setting	5 s – 60 Min.	Colour	white
Radial range	Ø 10 m (79 m²)	Base light function	Yes	SCOPE OF DELIVERY & WARRANTY	
Tangential range	Ø 10 m (79 m²)	Base light function detail	LED effect light	Manufacturer warranty	5 years
Mounting height	2 – 4 m	Base light function time	1-60 min	House number sheet included	No
Optimal mounting height	2,8 m	Main light adjustable	0 - 100 %	CERTIFICATES & EPREL	
CONNECTIVITY		Functions	Group parameterisation Manual ON / ON-OFF Neighbouring group function Orientation light Motions sensor Light sensor Encrypted communication Free selection of the light value in a luminaire group Adjustable fade time when switching on and off	EPREL category	Surrounded product with integrated light source


RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841068431
E-Nr. 941349329

Illustrations

TECHNICAL DRAWINGS



300 x 55 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------	------------------	---------------


RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

EAN 4007841068431
E-Nr. 941349329

SENSOR-SWITCHED LED INDOOR LIGHT


Wiring Diagrams

WIRING DIAGRAM 1



Slave/wireless master interconnection circuit diagram

WIRING DIAGRAM 2



Master circuit diagram

RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

EAN 4007841068431


E-Nr. 941349329

SENSOR-SWITCHED LED INDOOR LIGHT

Highlights



Including STEINEL LED system



Interconnectable and adjustable via Bluetooth



Impact-resistant material rated to IK07




Optional emergency light




Optional basic lighting level 0 - 100 %



Adjustable main light brightness (0 - 100%)



Modern plug-in terminals for straightforward installation



Metal shrouds for defining the direction of sensor detection

RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841068431
E-Nr. 941349329

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841087234	Adapter R-Serie für Notlichtweiche	Accessory
 4007841064143	Notlicht-Modul R-Serie	Accessory
 4007841084653	Funktaster PB2-Bluetooth	System components
 4007841084660	Funktaster PB4-Bluetooth	System components
 221386	Universal P-Set 3S	Suspension cable
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

068431

EAN

4007841068431

E-Number

941349329

Typ

RS PRO R10 basic SC Multi-pack (5 pcs.) warm white

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss