LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841086305
E-Nr. 535903118

- High-frequency corridor presence detector with square 360° detection
- Ideal for long corridors and hallways
- Range, individually digitally adjustable in two directions
- Setting Networking via Bluetooth
- Measurement of presence and brightness
- DALI addressing of up to 64 participants in max. 4 groups
- Operating modes: fully and semi-automatic, light sensor operation, night-time economy mode
- Time-based control with time- and day-dependent light profiles
- Flexible system expansion possible with system components

steinel

67 x 103 x 103 mm



LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841086305**
E-Nr. **535903118**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**67 x 103 x 103 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Supply voltage detail	**max. 64 users**
Control output DALI	**Addressable / broadcast 64 electronic ballasts**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**25 x 3 m (75 m²)**
Tangential range	**25 x 3 m (75 m²)**
Mounting height	**2 – 4 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**10 s – 60 Min.**
Base light function	**Yes**
Base light function time	**10 min, all day all night**
Main light adjustable	**Yes**
Functions	**Semi-/fully automatic Constant-lighting control Lighting scenario Master/slave override Neighbouring group function TouchDIM function Multizone Foldingdoor function**
Settings via	**Bluetooth Mesh**
With remote control	**No**
Twilight setting teach	**Yes**
Base light function in percent	**10 – 90 %**
Base light function percent from	**10 %**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -20 up to 50 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors corridor / aisle**
Colour	**white**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**

CERTIFICATES & EPREL

Certificates	**DALI-2**


LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841086305**
E-Nr. **535903118**

Illustrations

TECHNICAL DRAWINGS



67 x 103 x 103 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX


LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841086305
E-Nr. 535903118


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave interconnection circuit diagram

LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841086305**
E-Nr. **535903118**

Highlights



UV-resistant plastic

LuxMaster Hallway DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841086305**
E-Nr. **535903118**

Accessories

ORDERING INFORMATION

Art.-Nr.	086305
EAN	4007841086305
E-Number	535903118
Typ	**LuxMaster Hallway DALI-2 APC - concealed**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss