

HF 3360 PF - Aufputz rund

neva
lux

Product code 4007841033699

E-Nr. 535940567

- UV-resistant plastic
- Large terminal compartment
- Optional remote controls

neva
lux

126 x 52 mm



HF 3360 PF - Aufputz rund

Product code **4007841033699**
E-Nr. **535940567**

Technical Data

IDENTIFICATION		Detection		also through glass, wood and stud walls	Base light function	No
Version	Motion detectors	Detection angle	360 °		Main light adjustable	No
DIMENSIONS		Opening angle	180 °		Functions	Normal / test mode\nManual ON / ON-OFF
Dimensions Ø x H	126 x 52 mm	Sneak-under protection	Yes		Settings via	Remote control\nPotentiometers\nSmart Remote
ELECTRICAL		Segment-by-segment masking	No		With remote control	No
Mains connection	220 – 240 V / 50 – 60 Hz	Electronic scalability	Yes		Twilight setting teach	Yes
Power	2000 W	Mechanical scalability	No		HOUSING & MATERIAL	
Fluorescent lamps ECG	1500 W	Radial range	Ø 8 m (50 m²)		Protection class (IP)	IP54
Fluorescent lamps uncompensated	1000 VA	Tangential range	Ø 8 m (50 m²)		Ambient temperature	from -20 up to 50 °C
Fluorescent lamps series-compensated	400 VA	Mounting height	2,00 – 4,00 m		Mounting location	ceiling corner wall
Fluorescent lamps parallel-compensated	400 VA	Optimal mounting height	2,8 m		Application location	Indoors
Switching output 1 low-voltage halogen lamps	2000 VA	CONNECTIVITY			Mounting type	Surface wiring
LED lamps < 2 W	100 W	Networking	Yes		Material	Plastic
LED lamps > 2 W < 8 W	300 W	Type of networking	Master/master		Application room	Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell
LED lamps > 8 W	600 W	Networking via	Cable		Colour	white
Capacitive load in µF	176 µF	LIGHTING TECHNOLOGY			RAL colour	9003
SENSOR TECHNOLOGY		Soft light start	No		SCOPE OF DELIVERY & WARRANTY	
Max. mounting height	4,00 m	Continuous light	selectable, 4h		Manufacturer warranty	5 years
Sensor technology	High frequency	Constant light regulation	No		Corner wall bracket included	No
Transmission power	< 1 mW	SETTINGS				
HF technology	5,8 GHz	Twilight switch	Yes			
		Twilight setting	2 – 1000 lx			
		Time setting	5 s – 15 Min.			

HF 3360 PF - Aufputz rund

Product code **4007841033699**
E-Nr. **535940567**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

HF 3360 PF - Aufputz rund

Product code **4007841033699**
E-Nr. **535940567**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841056674	Schwarze Blende für den HF 3360 Aufputz eckig	Coverage
 4007841056698	Schwarze Blende für den HF 3360 Aufputz rund	Coverage
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841033699

E-Number

535940567

Typ

HF 3360 PF - Aufputz rund

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss