IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN 4007841079369
E-Nr. 535930910

steinel

108 x 120 x 120 mm



IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN 4007841079369
E-Nr. 535930910

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	108 x 120 x 120 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz

SENSOR TECHNOLOGY

Max. mounting height	10,00 m
Sensor technology	passive infrared
Detection angle	360 °
Opening angle	160 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	No
Mechanical scalability	Yes
Radial range	8 x 8 m (64 m²)
Tangential range	20 x 20 m (400 m²)
Detection planes	13
Switching zones	4800 switching zones
Mounting height	2,50 – 10,00 m
Presence range	8 x 8 m (64 m²)
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave
Networking quantity	max. 10 sensors
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS

Twilight switch	Yes
Time setting	30 s – 30 Min.
Base light function	No
Main light adjustable	No
Functions	Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF Constant-lighting control ON-OFF
Settings via	Remote control DIP switches Potentiometers Smart Remote
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -25 up to 55 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	changing room classroom conference room / meeting room duty room high-bay warehouse lecture hall multi-storey / underground car park open-plan office production facilities reception / lobby recreation room sports hall
Colour	white
RAL colour	9010

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN **4007841079369**
E-Nr. **535930910**

Illustrations

TECHNICAL DRAWINGS



108 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 10,00 m	2,8 m	10,00 m
BEREICH	OPTIMAL	MAX


IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN 4007841079369
E-Nr. 535930910


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN 4007841079369
E-Nr. 535930910


Highlights




4 pyros with DSP (Digital Signal Processing)



Optional remote controls



Optional surface-mounting adapter



Optional guard cage

IR Quattro HD 24m COM1 - in-ceiling installation white

PRESENCE DETECTOR

EAN **4007841079369**
E-Nr. **535930910**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	079369
EAN	4007841079369
E-Number	535930910
Typ	**IR Quattro HD 24m COM1 - in-ceiling installation white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss