

RS LED D1

neva
lux

Product code **4007841052522**

E-Nr. **941300459**

- Including STEINEL LED system
- LED ambient light
- Optional basic lighting level 10 %
- 4-hour manual override (optional)
- High-quality materials

neva
lux

300 x 300 x 65,5 mm



RS LED D1

Product code **4007841052522**
E-Nr. **941300459**

Technical Data

DIMENSIONS	
Dimensions L x W x H	300 x 300 x 65,5 mm
ELECTRICAL	
Mains connection	220 – 240 V , 50 / 60 Hz
Power	9,5 W
SENSOR TECHNOLOGY	
Sensor technology	High frequency
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Electronic scalability	Yes
Mechanical scalability	No
CONNECTIVITY	
Networking	No
LIGHTING TECHNOLOGY	
Colour temperature	3000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable, 4h
Luminous flux	795 lm
LIFETIME	
LED lifetime max. °C	50000 h
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Base light function	Yes
Base light function time	10/30 min, all night
HOUSING & MATERIAL	
Impact resistance	IK00
Protection class (IP)	IP20
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	3 years

RS LED D1

Product code **4007841052522**
E-Nr. **941300459**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841006341	Ersatzhaube für RS D1 S	Coverage

ORDERING INFORMATION

Art.-Nr.

4007841052522

E-Number

941300459

Typ

RS LED D1

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss