

HF 3360 PF - Unterputz rund

neva
lux

Product code 4007841033712

E-Nr. 535940767

- UV-resistant plastic
- Optional remote controls

neva
lux

124 x 64 mm



HF 3360 PF - Unterputz rund

Product code **4007841033712**
E-Nr. **535940767**

Technical Data

IDENTIFICATION		Detection		also through glass, wood and stud walls	Base light function	No
Version	Motion detectors	Detection angle		360 °	Main light adjustable	No
DIMENSIONS		Opening angle		180 °	Functions	Normal / test mode\nManual ON / ON-OFF
Dimensions Ø x H	124 x 64 mm	Sneak-under protection		Yes	Settings via	Remote control\nPotentiometers\nSmart Remote
ELECTRICAL		Segment-by-segment masking		No	With remote control	No
Mains connection	220 – 240 V / 50 – 60 Hz	Electronic scalability		Yes	Twilight setting teach	Yes
Power	2000 W	Mechanical scalability		No	HOUSING & MATERIAL	
Fluorescent lamps ECG	1500 W	Radial range		Ø 8 m (50 m²)	Protection class (IP)	IP20
Fluorescent lamps uncompensated	1000 VA	Tangential range		Ø 8 m (50 m²)	Ambient temperature	from -20 up to 50 °C
Fluorescent lamps series-compensated	400 VA	Mounting height		2,00 – 4,00 m	Mounting location	ceiling corner wall
Fluorescent lamps parallel-compensated	400 VA	Optimal mounting height		2,8 m	Application location	Indoors
Switching output 1 low-voltage halogen lamps	2000 VA	CONNECTIVITY			Mounting type	Concealed wiring
LED lamps < 2 W	100 W	Networking		Yes	Material	Plastic
LED lamps > 2 W < 8 W	300 W	Type of networking		Master/master	Application room	Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell
LED lamps > 8 W	600 W	Networking via		Cable	SCOPE OF DELIVERY & WARRANTY	
Capacitive load in µF	176 µF	LIGHTING TECHNOLOGY			Manufacturer warranty	5 years
SENSOR TECHNOLOGY		Soft light start		No	Corner wall bracket included	No
Max. mounting height	4,00 m	Continuous light		selectable, 4h		
Sensor technology	High frequency	Constant light regulation		No		
Transmission power	< 1 mW	SETTINGS				
HF technology	5,8 GHz	Twilight switch		Yes		
		Twilight setting		2 – 1000 lx		
		Time setting		5 s – 15 Min.		

HF 3360 PF - Unterputz rund

Product code **4007841033712**
E-Nr. **535940767**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

HF 3360 PF - Unterputz rund

Product code **4007841033712**
E-Nr. **535940767**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841056704	Schwarze Blende für den HF 3360 Unterputz rund	Coverage
 4007841056681	Schwarze Blende für den HF 3360 Unterputz eckig	Coverage

ORDERING INFORMATION

Art.-Nr.

4007841033712

E-Number

535940767

Typ

HF 3360 PF - Unterputz rund

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss