US 360 KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079628
E-Nr. 535934008

steinel

105 x 120 x 120 mm



US 360 KNX - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079628**
E-Nr. **535934008**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**105 x 120 x 120 mm**

ELECTRICAL

Mains connection	**24 – 29 V**

SENSOR TECHNOLOGY

Max. mounting height	**2,80 m**
Sensor technology	**Ultrasonic**
With motion detector	**Yes**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 10 m (79 m²)**
Tangential range	**Ø 6 m (28 m²)**
Mounting height	**2,50 – 2,8 m**
Presence range	**Ø 6 m (28 m²)**
US technology	**40 kHz**
Optimal mounting height	**3,5 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
KNX functions	**Photo-cell controller Basic light level function Light level HVAC output Constant-lighting control Light output 4x Presence output Day / night function Logic gate**
With bus coupler	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**0 s – 1092 Min.**
Base light function	**Yes**
Base light function time	**1-30 min, all night**
Main light adjustable	**0 - 100 %**
Settings via	**ETS software Remote control Bus Smart Remote**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -20 up to 55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**In-ceiling installation**
Material	**Plastic**
Application room	**Indoors WC / washroom classroom conference room / meeting room duty room function room / ancillary room one-person office open-plan office recreation room stairwell**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


US 360 KNX - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079628**
E-Nr. **535934008**

Illustrations

TECHNICAL DRAWINGS



105 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 2,8 m	3,5 m	2,80 m
BEREICH	OPTIMAL	MAX

US 360 KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079628
E-Nr. 535934008


Highlights




Optional remote controls



Smart Remote remote control optional



Optional surface-mounting adapter



Optional guard cage

US 360 KNX - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079628**
E-Nr. **535934008**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841593018	**Service Fernbedienung RC6 KNX**	Accessory
	4007841592912	**Nutzer Fernbedienung RC7 KNX**	Accessory

ORDERING INFORMATION

Art.-Nr.	079628
EAN	4007841079628
E-Number	535934008
Typ	**US 360 KNX - in-ceiling installation**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss