

L 920 LED anthrazit

neva
lux

Product code **4007841056483**

E-Nr. **941200149**

- Intelligent soft light start
- Interconnectable by cable
- 4-hour manual override (optional)
- High-quality aluminium
- Setting options protected from the weather and from outside influences

neva
lux

225 x 95 x 94 mm



L 920 LED anthrazit

Product code **4007841056483**
E-Nr. **941200149**

Technical Data

IDENTIFICATION			
Variant	Anthracite	Radial range	r = 2 m (5 m²) / r = 4 m (20 m²)
DIMENSIONS		Tangential range	r = 5 m (31 m²) / r = 12 m (176 m²)
Dimensions L x W x H	225 x 95 x 94 mm	CONNECTIVITY	
ELECTRICAL		Networking	Yes
Mains connection	220 – 240 V , 50 / 60 Hz	LIGHTING TECHNOLOGY	
Power	10 W	Colour temperature	3000 K
SENSOR TECHNOLOGY		Colour rendering index	80-89
Max. mounting height	2,50 m	With illuminant	Yes, STEINEL LED system
Sensor technology	passive infrared	Illuminant	LED cannot be replaced
With motion detector	Yes	Base	without
Detection angle	140 °	LED cooling system	Passive Thermo Control
Sneak-under protection	No	Soft light start	Yes
Segment-by-segment masking	No	Continuous light	selectable, 4h
Electronic scalability	Yes	Luminous flux	516 lm
Mechanical scalability	No	LIFETIME	
		LED lifetime max. °C	50000 h
		SETTINGS	
		Twilight switch	Yes
		Twilight setting	2 – 20 lx
		Time setting	120 sec – 15 min
		Base light function	Yes
		Base light function time	10-30 min, all night
		With remote control	No
		HOUSING & MATERIAL	
		Impact resistance	IK00
		Protection class (IP)	IP44
		Protection class	II
		Ambient temperature	-20 – 40 °C
		Housing material	Aluminium
		Cover material	Plastic, opal
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	3 years

L 920 LED anthrazit

Product code **4007841056483**
E-Nr. **941200149**

Illustrations

MOUNTING HEIGHT

2,50 m MAX

L 920 LED anthrazit

Product code **4007841056483**E-Nr. **941200149**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841056483

E-Number 941200149

Typ **L 920 LED anthrazit**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss