

RS PRO 5800 LED Slave



Product code **4007841007669**

E-Nr. **941331979**

- Including STEINEL LED system
- Optional remote control
- Interconnectable via DALI, max. 15 slaves? / master
- Impact-resistant material rated to IK07
- Intelligent swarm function

neva
lux

1,278 x 105 x 105 mm



RS PRO 5800 LED Slave

Product code 4007841007669
E-Nr. 941331979

Technical Data

IDENTIFICATION		Colour rendering index		80-89	Time setting		5 sec – 15 min
Variant	Slave	With illuminant	Yes, STEINEL LED system		Functions	Group parameterisation, Neighbouring-light function, Presence function	
DIMENSIONS		Illuminant	LED cannot be replaced				
Dimensions L x W x H	1,278 x 105 x 105 mm	Base	without		HOUSING & MATERIAL		
ELECTRICAL		LED cooling system	Passive Thermo Control		Impact resistance	IK07	
Mains connection	220 – 240 V , 50 / 60 Hz	Soft light start	Yes		Protection class (IP)	IP66	
Power	33 W	Luminous flux	4065 lm		Protection class	I	
SENSOR TECHNOLOGY		LIFETIME			Ambient temperature	-20 – 30 °C	
With motion detector	No	LED lifetime max. °C	50000 h		Housing material	Plastic	
LIGHTING TECHNOLOGY		Luminous flux decline per LM80	L70B10		Cover material	Plastic, opal	
Colour temperature	4000 K	SETTINGS			SCOPE OF DELIVERY & WARRANTY		
LED colour deviation	SDCM3	Twilight switch	No		Manufacturer warranty	5 years	

RS PRO 5800 LED Slave

Product code **4007841007669**
E-Nr. **941331979**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841008925	RC10 für RS PRO 5800/5850 LED	
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007669

E-Number

941331979

Typ

RS PRO 5800 LED Slave

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss