

L 115 S silber

neva
lux

Product code **4007841657512**

- Optional basic lighting level 0 - 50 %
- UV-resistant plastic
- Intelligent soft light start
- 4-hour manual override (optional)

neva
lux

330 x 215 x 257 mm



L 115 S silber

Product code **4007841657512**

Technical Data

IDENTIFICATION

Variant Silver

DIMENSIONS

Dimensions L x W x H **330 x 215 x 257 mm**

ELECTRICAL

Mains connection 230 – 240 V , 50 / 60 Hz

Power	60 W
-------	------

SENSOR TECHNOLOGY

Sensor technology **passive infrared**

With motion detector Yes

Detection angle	240 °
-----------------	-------

Opening angle **120 °**

Sneak-under protection	Yes
------------------------	-----

Segment-by-segment masking	Yes
----------------------------	-----

Electronic scalability	No
------------------------	----

Mechanical scalability	No
------------------------	----

Radial range $r = 12 \text{ m}$ (302 m²)

Tangential range **r = 12 m (302 m²)**

LIGHTING TECHNOLOGY

With illuminant No

illuminant	All-purpose lamp
------------	------------------

Base E27

Soft light start	Yes
------------------	-----

Continuous light selectable, 4h

SETTINGS

Twilight switch Yes

Twilight setting	2 – 2000 lx
------------------	-------------

Time setting **5 sec – 15 min**

Base light function	Yes
---------------------	-----

Settings via Potentiometers

HOUSING & MATERIAL

Impact resistance	IK00
-------------------	------

Protection class (IP)	IP44
-----------------------	------

Protection class	II
------------------	----

Ambient temperature -20 – 40 °C

Housing material	Plastic
------------------	---------

Cover material	Glass transparent
----------------	-------------------

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty **3 years**

L 115 S silber

Product code 4007841657512

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841001681	Ersatzglas für L 115 S	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841657512

Typ

L 115 S silber

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss