

RS PRO 5850 LED Sensor



Product code **4007841007676**

E-Nr. **941332979**

- Including STEINEL LED system
- Optional remote control
- Interconnectable via DALI, max. 15 slaves? / master
- Impact-resistant material rated to IK07
- Intelligent swarm function

neva
lux

1,583 x 105 x 105 mm



RS PRO 5850 LED Sensor

Product code **4007841007676**
E-Nr. **941332979**

Technical Data

IDENTIFICATION		Mechanical scalability		No	SETTINGS	
Variant	Sensor	LIGHTING TECHNOLOGY			Twilight switch	Yes
DIMENSIONS		Colour temperature		4000 K	Functions	Group parameterisation, Neighbouring-light function, Presence function
Dimensions L x W x H	1,583 x 105 x 105 mm	LED colour deviation		SDCM3		
ELECTRICAL		Colour rendering index		80-89		
Mains connection	220 – 240 V , 50 / 60 Hz	With illuminant	Yes, STEINEL LED system		Impact resistance	IK07
Power	45 W	Illuminant	LED cannot be replaced		Protection class (IP)	IP66
SENSOR TECHNOLOGY		Base	without		Protection class	I
Sensor technology	High frequency	LED cooling system	Passive Thermo Control		Ambient temperature	-20 – 30 °C
With motion detector	Yes	Soft light start	Yes		Housing material	Plastic
Detection	also through glass, wood and stud walls	Luminous flux	5570 lm		Cover material	Plastic, opal
		LIFETIME			SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	LED lifetime max. °C	50000 h		Manufacturer warranty	5 years
Opening angle	160 °	Luminous flux decline per LM80	L70B10			
Electronic scalability	Yes					

RS PRO 5850 LED Sensor

Product code **4007841007676**
E-Nr. **941332979**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841008925	RC10 für RS PRO 5800/5850 LED	
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007676

E-Number

941332979

Typ

RS PRO 5850 LED Sensor

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss