

IS 3360 MX Highbay DALI-2 Input Device - UP eckig

neva
lux

Product code 4007841057381

E-Nr. 535946805

neva
lux

94 x 94 x 78 mm



IS 3360 MX Highbay DALI-2 Input Device - UP eckig

Product code 4007841057381
E-Nr. 535946805

Technical Data

IDENTIFICATION					
Variant	DALI-2 IPD - concealed, sq.	Segment-by-segment masking	Yes	Twilight setting teach	Yes
Version	Motion detectors	Electronic scalability	No	HOUSING & MATERIAL	
DIMENSIONS		Radial range	Ø 14 m (154 m²)	Protection class (IP)	IP20
Dimensions L x W x H	94 x 94 x 78 mm	Tangential range	Ø 36 m (1018 m²)	Ambient temperature	-20 – 50 °C
ELECTRICAL		Switching zones	1416 switching zones	Mounting location	ceiling
Mains connection	12 – 22,5 V	Mounting height	4,00 – 14,00 m	Application location	Indoors
Switching output 1 potential-free	No	Optimal mounting height	12 m	Mounting type	Concealed wiring
Control output DALI	Addressable/slave	CONNECTIVITY		Material	Plastic
SENSOR TECHNOLOGY		Networking	Yes	Colour	white
Sensor technology	passive infrared	With bus coupler	Yes	RAL colour	9003
Detection angle	360 °	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Opening angle	45 °	Twilight setting	2 – 1000 lx	Manufacturer warranty	5 years
Sneak-under protection	Yes	Base light function	No	OTHER	
		With remote control	No	Application, location, room	high-bay warehouse, sports hall

IS 3360 MX Highbay DALI-2 Input Device - UP eckig

Product code **4007841057381**
E-Nr. **535946805**

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL
---------------------------	-----------------

IS 3360 MX Highbay DALI-2 Input Device - UP eckig

Product code **4007841057381**
E-Nr. **535946805**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841057381
E-Number	535946805
Typ	IS 3360 MX Highbay DALI-2 Input Device - UP eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	