

RS PRO Connect R30 Q SL warmweiss



Product code **4007841057213**

E-Nr. **941301669**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Backlight function
- Optional main light level 50 - 100%
- Modern plug-in terminals for straightforward installation

neva
lux

55 x 350 x 350 mm



RS PRO Connect R30 Q SL warmweiss

Product code **4007841057213**
E-Nr. **941301669**

Technical Data

IDENTIFICATION		With illuminant		Yes, STEINEL LED system	Base light function detail		LED Backlight
Variant	warm white	Illuminant		LED cannot be replaced	Functions		Backlight
DIMENSIONS		Base		without	Settings via		Bluetooth
Dimensions L x W x H	55 x 350 x 350 mm	LED cooling system		Passive Thermo Control	With remote control		No
ELECTRICAL		Soft light start		Yes	HOUSING & MATERIAL		
Mains connection	220 – 240 V / 50 – 60 Hz	Continuous light		selectable	Impact resistance		IK07
Power	24,5 W	Luminous flux		3070 lm	Protection class (IP)		IP40
SENSOR TECHNOLOGY		LIFETIME			Protection class		II
With motion detector	No	LED lifetime max. °C		50000 h	Ambient temperature		-20 – 40 °C
LIGHTING TECHNOLOGY		Luminous flux decline per LM80		L80B50	Housing material		Plastic
Colour temperature	3000 K	LED lifespan (25 °C)		60000 h	Cover material		PC, opal
LED colour deviation	SDCM3	SETTINGS			SCOPE OF DELIVERY & WARRANTY		
Colour rendering index	80-89	Twilight switch		No	Manufacturer warranty		5 years

RS PRO Connect R30 Q SL warmweiss

Product code **4007841057213**
E-Nr. **941301669**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841057220	RS PRO Connect R30 Q warmweiss	

ORDERING INFORMATION

Art.-Nr.

4007841057213

E-Number

941301669

Typ

RS PRO Connect R30 Q SL warmweiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss