

fayola 205 V2 3CCT DALI

SERIE FAYOLA V2

neva
lux

Product code **221450**

- Versatile use in commercial properties and in the hotel industry
- 3 light colors selectable (2700, 4000 or 5700 Kelvin)
- Brightness adjustable thanks to DALI-2 driver
- IP44 protection class for use in wet rooms and protected outdoor areas
- Wide beam diffuser (90 °)
- Very good glare control values thanks to microprismatic diffuser
- Available in 5 different sizes

neva
lux

228 x 45 mm



fayola 205 V2 3CCT DALI

SERIE FAYOLA V2

Product code 221450

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø x H	228 x 45 mm	LED colour deviation	SDCM3	Protection class (IP)	IP44
Drill hole	205 mm	Colour rendering index	80-89	Protection class	II
ELECTRICAL		Illuminant	LED	Ambient temperature	-20...45 °C
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	3570 lm	Housing material	Aluminum
Power	35 W	Beam angle	90°	Cover material	Microprismatic acrylic glass
Replaceable driver	Yes	Luminaire luminous efficacy	102 lm/W	Mounting type	In-ceiling installation
Type of wiring	Ending	Glare value	UGR<24	Colour	white
LED rated current	800 mA	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
With motion detector	No	SETTINGS		CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		DALI dimming	Yes	EPREL energy efficiency class	E
Colour temperature	2700 / 4000 / 5700 K				

fayola 205 V2 3CCT DALI

SERIE FAYOLA V2

Product code 221450

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221447	fayola 125 V2 3CCT DALI	
 221448	fayola 150 V2 3CCT DALI	
 221449	fayola 175 V2 3CCT DALI	
 221446	fayola 100 V2 3CCT DALI	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221450

Typ

fayola 205 V2 3CCT DALI

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss