

# HF 3360 COM1 - Unterputz eckig

**neva**  
**lux**

Product code 4007841033675

E-Nr. 535940660

- UV-resistant plastic
- Optional remote controls

**neva**  
**lux**

64 x 94 x 94 mm



# HF 3360 COM1 - Unterputz eckig

Product code **4007841033675**

E-Nr. **535940660**

## Technical Data

| IDENTIFICATION                                     |                          |
|----------------------------------------------------|--------------------------|
| Version                                            | Motion detectors         |
| DIMENSIONS                                         |                          |
| Dimensions L x W x H                               | 64 x 94 x 94 mm          |
| ELECTRICAL                                         |                          |
| Mains connection                                   | 220 – 240 V / 50 – 60 Hz |
| Power                                              | 2000 W                   |
| Switching output 1 resistive                       | 2000 W                   |
| Fluorescent lamps ECG                              | 1500 W                   |
| Fluorescent lamps uncompensated                    | 1000 VA                  |
| Fluorescent lamps series-compensated               | 400 VA                   |
| Fluorescent lamps parallel-compensated             | 400 VA                   |
| Switching output 1 low-voltage halogen lamps       | 2000 VA                  |
| LED lamps < 2 W                                    | 100 W                    |
| LED lamps > 2 W < 8 W                              | 300 W                    |
| LED lamps > 8 W                                    | 600 W                    |
| Capacitive load in µF                              | 176 µF                   |
| Switching output 1 number of LED/fluorescent lamps | 8 pcs.                   |
| SENSOR TECHNOLOGY                                  |                          |
| Max. mounting height                               | 4,00 m                   |
| Sensor technology                                  | High frequency           |

| Transmission power         | < 1 mW                                  |
|----------------------------|-----------------------------------------|
| HF technology              | 5,8 GHz                                 |
| Detection                  | also through glass, wood and stud walls |
| Detection angle            | 360 °                                   |
| Opening angle              | 180 °                                   |
| Sneak-under protection     | Yes                                     |
| Segment-by-segment masking | No                                      |
| Electronic scalability     | Yes                                     |
| Mechanical scalability     | No                                      |
| Radial range               | Ø 8 m (50 m²)                           |
| Tangential range           | Ø 8 m (50 m²)                           |
| Mounting height            | 2,00 – 4,00 m                           |
| Optimal mounting height    | 2,8 m                                   |
| CONNECTIVITY               |                                         |
| Networking                 | Yes                                     |
| Type of networking         | Master/master                           |
| Networking via             | Cable                                   |
| LIGHTING TECHNOLOGY        |                                         |
| Soft light start           | No                                      |
| Continuous light           | selectable, 4h                          |
| Constant light regulation  | No                                      |
| SETTINGS                   |                                         |
| Twilight switch            | Yes                                     |
| Twilight setting           | 2 – 1000 lx                             |

| Time setting                 | 5 s – 15 Min.                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------|
| Base light function          | No                                                                                                 |
| Main light adjustable        | No                                                                                                 |
| Functions                    | Normal / test mode\nManual ON / ON-OFF                                                             |
| Settings via                 | Remote control\nPotentiometers\nSmart Remote                                                       |
| With remote control          | No                                                                                                 |
| Twilight setting teach       | Yes                                                                                                |
| HOUSING & MATERIAL           |                                                                                                    |
| Protection class (IP)        | IP20                                                                                               |
| Ambient temperature          | from -20 up to 50 °C                                                                               |
| Mounting location            | ceiling corner wall                                                                                |
| Application location         | Indoors                                                                                            |
| Mounting type                | Concealed wiring                                                                                   |
| Material                     | Plastic                                                                                            |
| Application room             | Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell |
| Colour                       | white                                                                                              |
| RAL colour                   | 9003                                                                                               |
| SCOPE OF DELIVERY & WARRANTY |                                                                                                    |
| Manufacturer warranty        | 5 years                                                                                            |
| Corner wall bracket included | No                                                                                                 |

HF 3360 COM1 - Unterputz eckig

Product code **4007841033675**  
E-Nr. **535940660**

Illustrations

MOUNTING HEIGHT

|                          |                  |               |
|--------------------------|------------------|---------------|
| 2,00 – 4,00 m<br>BEREICH | 2,8 m<br>OPTIMAL | 4,00 m<br>MAX |
|--------------------------|------------------|---------------|

HF 3360 COM1 - Unterputz eckig

Product code **4007841033675**  
E-Nr. **535940660**

Accessories

| ARTICLE NUMBER                                                                                    | DESCRIPTION                                     | CATEGORY       |
|---------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------|
|  4007841009151   | Smart Remote                                    | Accessory      |
|  4007841559410   | Service Fernbedienung RC8                       | Accessory      |
|  4007841035174    | Eckwandhalter 3000 weiss                        | Corner adapter |
|  4007841056681   | Schwarze Blende für den HF 3360 Unterputz eckig | Coverage       |
|  4007841056704 | Schwarze Blende für den HF 3360 Unterputz rund  | Coverage       |

ORDERING INFORMATION

Art.-Nr.

4007841033675

E-Number

535940660

Typ

HF 3360 COM1 - Unterputz eckig

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss