

PD IR 4360-8 KNX - surface white

MOTION AND PRESENCE DETECTOR

neva
lux

EAN 4007841086176

E-Nr. 535900039

- Our series for the common ranges
- Presence detector with 8 m motion detection and 6 m presence detection for integration into a KNX bus system
- Ideal for offices, meeting rooms or passageways
- Includes insertable cover caps to limit the detection range
- Installation-friendly, thanks to round design and modular system with magnetic plug-in connection
- Start of programming mode from a distance via Smart Remote remote control via app
- External approval and measurement in accordance with sensNORM

● steinel

129 x 65 mm



PD IR 4360-8 KNX - surface white

MOTION AND PRESENCE DETECTOR

EAN 4007841086176

E-Nr. 535900039

Technical Data

IDENTIFICATION		HOUSING & MATERIAL	
Version	Motion and Presence Detector	Protection class (IP)	IP54
DIMENSIONS		Ambient temperature	from -20 up to 50 °C
Dimensions L x W x H	65 x 129 x 129 mm	Housing material	Plastic
Dimensions Ø x H	129 x 65 mm	Cover material	Other
SENSOR TECHNOLOGY		Cover material (scope of delivery)	shrouds
Max. mounting height	4,00 m	Mounting location	ceiling
Sensor technology	passive infrared	Application location	Indoors
With motion detector	Yes	Mounting type	Surface wiring
Detection angle	360 °	Material	Plastic
Sneak-under protection	Yes	Application room	Indoors function room / ancillary room one-person office warehouse
Segment-by-segment masking	Yes	Colour	white
Electronic scalability	No	RAL colour	9010
Mechanical scalability	No	SCOPE OF DELIVERY & WARRANTY	
Radial range	Ø 4.5 m (16 m²)	Manufacturer warranty	5 years
Tangential range	Ø 8 m (50 m²)	Corner wall bracket included	No
Switching zones	492 switching zones		
Mounting height	2 – 4 m		
CONNECTIVITY			
Presence range	Ø 6 m (28 m²)		
Optimal mounting height	2,8 m		
Type of networking	Master/master		
Networking via	Cable		
KNX functions	Light level Light output 2x Constant-lighting control Photo-cell controller Basic light level function HVAC output Logic gate Presence output Sabotage protection Day / night function		
With bus coupler	Yes		
SETTINGS			
Twilight setting	2 – 800 lx		
Time setting	10 s – 1092 Min.		
Functions	Motions sensor Light sensor Presence function Presence detector logic		
Settings via	Smart Remote ETS software Bus		
With remote control	No		
Twilight setting teach	Yes		

PD IR 4360-8 KNX - surface white


MOTION AND PRESENCE DETECTOR

EAN 4007841086176

E-Nr. 535900039

Illustrations

TECHNICAL DRAWINGS



129 x 65 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
---------------------------------------	-------------------------------------	----------------------------------

PD IR 4360-8 KNX - surface white

MOTION AND PRESENCE DETECTOR

EAN 4007841086176
E-Nr. 535900039

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841079543	Deckeneinbau-Adapter Deckeneinbau	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

086176

EAN

4007841086176

E-Number

535900039

Typ

PD IR 4360-8 KNX - surface white

nevalux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss