IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN 4007841592301
E-Nr. 535932605

steinel

71 x 120 x 120 mm



IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN **4007841592301**
E-Nr. **535932605**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**71 x 120 x 120 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**2000 W**
Fluorescent lamps ECG	**1500 W**
Fluorescent lamps uncompensated	**1000 VA**
Fluorescent lamps series-compensated	**1000 VA**
Fluorescent lamps parallel-compensated	**1000 VA**
Switching output 1 low-voltage halogen lamps	**2000 VA**
LED lamps < 2 W	**100 W**
LED lamps > 2 W < 8 W	**300 W**
LED lamps > 8 W	**600 W**
Capacitive load in µF	**176 µF**

SENSOR TECHNOLOGY

Max. mounting height	**8,00 m**
Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**100 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**No**
Mechanical scalability	**Yes**
Radial range	**5 x 5 m (25 m²)**
Tangential range	**7 x 7 m (49 m²)**
Detection planes	**13**
Switching zones	**1760 switching zones**
Mounting height	**2,50 – 8,00 m**
Presence range	**4 x 4 m (16 m²)**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
Networking quantity	**max. 10 sensors**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**30 s – 30 Min.**
Base light function	**No**
Main light adjustable	**No**
Functions	**Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF**
Settings via	**Remote control DIP switches Potentiometers Smart Remote**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from 0 up to 40 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Application room	**Indoors changing room conference room / meeting room duty room function room / ancillary room kitchenette one-person office recreation room**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN **4007841592301**
E-Nr. **535932605**

Illustrations

TECHNICAL DRAWINGS



71 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 8,00 m	2,8 m	8,00 m
BEREICH	OPTIMAL	MAX


IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN **4007841592301**
E-Nr. **535932605**


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN 4007841592301
E-Nr. 535932605

Highlights



Optional remote controls

IR Quattro 8m COM1 - Surface wiring

PRESENCE DETECTOR

EAN 4007841592301
E-Nr. 535932605

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	592301
EAN	4007841592301
E-Number	535932605
Typ	**IR Quattro 8m COM1 - Surface wiring**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss