IS 345 MX Highbay DALI-2 IPD - concealed, sq.

MOTION DETECTOR

EAN 4007841057404
E-Nr. 535942005

95 x 95 x 78 mm



IS 345 MX Highbay DALI-2 IPD - concealed, sq.

MOTION DETECTOR

EAN 4007841057404
E-Nr. 535942005

Technical Data

IDENTIFICATION

Variant	DALI-2 IPD - concealed, sq.
Version	Motion detectors

DIMENSIONS

Dimensions L × W × H	95 x 95 x 78 mm

ELECTRICAL

Mains connection	12 – 22,5 V / 50 – 60 Hz
Control output DALI	Addressable/slave

SENSOR TECHNOLOGY

Sensor technology	passive infrared
Detection angle	360 °
Opening angle	45 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	12 x 6 m (72 m²)
Tangential range	23 x 6 m (138 m²)
Switching zones	280 switching zones
Mounting height	4,00 – 14,00 m
Optimal mounting height	12 m

CONNECTIVITY

Networking	Yes
With bus coupler	Yes
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Constant light regulation	No

SETTINGS

Twilight setting	2 – 1000 lx
Time setting	1 s – 60 Min.
Base light function	Yes
Base light function time	1-30 min, all night
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	-20 – 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	high-bay warehouse

IS 345 MX Highbay DALI-2 IPD - concealed, sq.

MOTION DETECTOR

EAN 4007841057404
E-Nr. 535942005

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL

IS 345 MX Highbay DALI-2 IPD - concealed, sq.

MOTION DETECTOR

EAN 4007841057404
E-Nr. 535942005

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841057404
EAN	4007841057404
E-Number	535942005
Typ	**IS 345 MX Highbay DALI-2 IPD - concealed, sq.**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss