

# IR Quattro SLIM COM2

**neva**  
**lux**

Product code **4007841593513**

E-Nr. **535931405**

- Extremely slim overall height
- High-quality retina lens
- Can only be set by optional remote control RC8

**neva**  
**lux**

77 x 77 x 60 mm



IR Quattro SLIM COM2

Product code **4007841593513**  
E-Nr. **535931405**

Technical Data

|                              |                          |                           |                                             |                             |                              |  |     |                                         |
|------------------------------|--------------------------|---------------------------|---------------------------------------------|-----------------------------|------------------------------|--|-----|-----------------------------------------|
| IDENTIFICATION               |                          | Mechanical scalability    |                                             | No                          | Base light function          |  | No  |                                         |
| Variant                      | COM2                     | Range detail              | Retina lens and hexagonal Fresnel structure |                             | With remote control          |  | No  |                                         |
| Version                      | Presence detector        |                           |                                             |                             | Twilight setting teach       |  | Yes |                                         |
| DIMENSIONS                   |                          | Radial range              |                                             | 4 x 4 m (16 m²)             | HOUSING & MATERIAL           |  |     |                                         |
| Dimensions L x W x H         |                          | Tangential range          |                                             | 4 x 4 m (16 m²)             | Protection class (IP)        |  |     | IP20                                    |
| ELECTRICAL                   |                          | Switching zones           |                                             | 260 switching zones         | Ambient temperature          |  |     | 0 – 40 °C                               |
| Mains connection             | 120 – 250 V , 50 / 60 Hz | Mounting height           |                                             | 2,50 – 4,00 m               | Mounting location            |  |     | ceiling                                 |
| Switching output 1 resistive | 2000 W                   | Presence range            |                                             | 4 x 4 m (16 m²)             | Application location         |  |     | Indoors                                 |
| Supply voltage detail        | 500 VA max., 120 V       | Optimal mounting height   |                                             | 2,8 m                       | Mounting type                |  |     | Installation                            |
| SENSOR TECHNOLOGY            |                          | CONNECTIVITY              |                                             |                             | Material                     |  |     | Plastic                                 |
| Sensor technology            | passive infrared         | Networking                |                                             | Yes                         | Colour                       |  |     | white                                   |
| Detection angle              | 360 °                    | Type of networking        |                                             | Master/slave, Master/master | RAL colour                   |  |     | 9010                                    |
| Sneak-under protection       | Yes                      | LIGHTING TECHNOLOGY       |                                             |                             | SCOPE OF DELIVERY & WARRANTY |  |     |                                         |
| Segment-by-segment masking   | No                       | Constant light regulation |                                             | No                          | Manufacturer warranty        |  |     | 5 years                                 |
| Electronic scalability       | No                       | SETTINGS                  |                                             |                             | OTHER                        |  |     |                                         |
|                              |                          | Twilight setting          |                                             | 10 – 1000 lx                | Application, location, room  |  |     | One-person office, classroom, side room |
|                              |                          | Time setting              |                                             | 30 sec – 30 min             |                              |  |     |                                         |

IR Quattro SLIM COM2

Product code **4007841593513**  
E-Nr. **535931405**

Illustrations

MOUNTING HEIGHT

|                          |                  |
|--------------------------|------------------|
| 2,50 – 4,00 m<br>BEREICH | 2,8 m<br>OPTIMAL |
|--------------------------|------------------|

IR Quattro SLIM COM2

Product code **4007841593513**  
E-Nr. **535931405**

Accessories

| ARTICLE NUMBER                                                                                 | DESCRIPTION               | CATEGORY  |
|------------------------------------------------------------------------------------------------|---------------------------|-----------|
|  4007841559410 | Service Fernbedienung RC8 | Accessory |
|  4007841009151 | Smart Remote              | Accessory |

ORDERING INFORMATION

Art.-Nr.

4007841593513

E-Number

535931405

Typ

IR Quattro SLIM COM2

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss