

Dual US DIM

neva
lux

Product code **4007841007867**

- Optional remote controls
- Optional surface-mounting adapter
- Optional guard cage

neva
lux

120 x 120 x 73 mm



Dual US DIM

Product code 4007841007867

Technical Data

IDENTIFICATION					
Variant	DIM	Radial range	20 x 3 m (60 m²)	Twilight setting teach	Yes
Version	Presence detector	Tangential range	20 x 3 m (60 m²)	HOUSING & MATERIAL	
		Mounting height	2,50 – 3,50 m	Protection class (IP)	IP20
DIMENSIONS		Optimal mounting height	2,8 m	Ambient temperature	-25 – 55 °C
Dimensions L × W × H		CONNECTIVITY		Mounting location	ceiling
		Networking	Yes	Application location	Indoors
ELECTRICAL		Type of networking	Master/slave, Master/master	Mounting type	Concealed wiring
Mains connection	220 – 240 V , 50 / 60 Hz	LIGHTING TECHNOLOGY		Material	Plastic
Number of ECGs DIM interface	50			Colour	white
		Constant light regulation	Yes	RAL colour	9010
SENSOR TECHNOLOGY		SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Sensor technology		Twilight setting	100 – 1000 lx	Manufacturer warranty	5 years
Detection angle	360 °	Time setting	30 sec – 30 min	OTHER	
Sneak-under protection	Yes	Base light function	Yes		
Electronic scalability	Yes	With remote control	Yes	Application, location, room	corridor, aisle
Mechanical scalability	No				

Dual US DIM

Product code 4007841007867

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
---	-------------------------------------

Dual US DIM

Product code 4007841007867

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007867

Typ

Dual US DIM

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss