

# elani P3200 TW

ELANI

neva  
lux

Product code **221114**

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva  
lux

3140 x 60 x 80 mm



elani P3200 TW

ELANI

Product code **221114**

## Technical Data

## DIMENSIONS

|                      |                   |
|----------------------|-------------------|
| Dimensions L x W x H | 3140 x 60 x 80 mm |
| Suspension length    | 2000 mm           |

## ELECTRICAL

|                    |                             |
|--------------------|-----------------------------|
| Mains connection   | 200...240 V / 50 – 60 Hz    |
| Power              | 97 W                        |
| Replaceable driver | Yes                         |
| Type of wiring     | Suitable for through wiring |

## SENSOR TECHNOLOGY

|                      |    |
|----------------------|----|
| With motion detector | No |
| With light sensor    | No |

## LIGHTING TECHNOLOGY

|                        |               |
|------------------------|---------------|
| Colour temperature     | 3000...5600 K |
| LED colour deviation   | SDCM3         |
| Colour rendering index | 80-89         |

| Illuminant    | Yes, LED-System               |
|---------------|-------------------------------|
| Luminous flux | 12560 lm (Down 8164, Up 4396) |

|                             |                    |
|-----------------------------|--------------------|
| Beam angle                  | Down 105°, Up 115° |
| Luminaire luminous efficacy | 129 lm/W           |
| Glare value                 | UGR < 22           |

## LIFETIME

LED lifespan (25 °C) 70000 h

## SETTINGS

|              |     |
|--------------|-----|
| DALI dimming | Yes |
|--------------|-----|

|                      |    |
|----------------------|----|
| With emergency light | No |
|----------------------|----|

|                                       |     |
|---------------------------------------|-----|
| Suitable for light band configuration | Yes |
|---------------------------------------|-----|

|                         |     |
|-------------------------|-----|
| Direct/indirect ratio   | Yes |
| separately controllable |     |

|                               |     |
|-------------------------------|-----|
| Constant light output control | Yes |
|-------------------------------|-----|

## HOUSING & MATERIAL

|                       |      |
|-----------------------|------|
| Protection class (IP) | IP20 |
|-----------------------|------|

|                  |    |
|------------------|----|
| Protection class | II |
|------------------|----|

|                     |             |
|---------------------|-------------|
| Ambient temperature | -20...45 °C |
|---------------------|-------------|

|                  |           |
|------------------|-----------|
| Housing material | Aluminium |
|------------------|-----------|

|                |                    |
|----------------|--------------------|
| Cover material | Acrylic glass opal |
|----------------|--------------------|

| Mounting type | Ceiling pendant |
|---------------|-----------------|
|---------------|-----------------|

| Colour | Aluminium |
|--------|-----------|
|--------|-----------|

## SCOPE OF DELIVERY & WARRANTY

|                       |         |
|-----------------------|---------|
| Manufacturer warranty | 5 years |
|-----------------------|---------|

CERTIFICATES & EPREL

EPREL energy efficiency class

elani P3200 TW

ELANI

Product code 221114

Accessories

| ARTICLE NUMBER                                                                            | DESCRIPTION                  | CATEGORY                   |
|-------------------------------------------------------------------------------------------|------------------------------|----------------------------|
|  221102   | elani Diffusor 3200 CDP      | Cover                      |
|  221108   | Emergency Package 1h (Astra) | Emergency lighting         |
|  221343   | elani Connector 90°          | Coupler/connector L-shape  |
|  221107  | elani Link                   | Coupler/connector straight |
|  221397 | elani Color RAL_NCS_3200     | Other                      |
|  221997 | elani WM-Set 3B              | Mounting kit               |

ORDERING INFORMATION

Art.-Nr.

221114

Typ

elani P3200 TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss